

440/65 R 28 131D TL TRAXION 65

EAN CODE: **8714692360497**
SKU CODE: **LB44652831DT6LA00**
ECE NUMBER: **E4-106R-003345**



Recommended rim width:	DW14L
Permitted rim width:	W13/W14L/ (D)W15L
Nominal Tyre Pressure:	160 kpa
Section Width:	440 mm
Outer Diameter:	1290 mm
Static Loaded Radius:	590 mm
Rolling Circumference:	3870 mm
SRI:	625
Tread depth:	40 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1615	1830	2055	2275	2500	2675	2820	2995
10H	1340	1555	1765	1950	2105	2245		
25	1380	1600	1820	2005	2165	2310		
30	1340	1555	1765	1950	2105	2245		
40		1480	1680	1855	2000	2135		
50		1420	1615	1780	1920	2050		
65			1535	1695	1830	1950		
70			1400	1540	1665	1775		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES