

# 480/65 R 24 133D TL TRAXION 65

EAN CODE: **8714692360473**

SKU CODE: **LB48652433DT6LA00**

ECE NUMBER: **E4-106R-003343**



|                        |                    |
|------------------------|--------------------|
| Recommended rim width: | <b>DW15L</b>       |
| Permitted rim width:   | <b>(D)W14/W15L</b> |
| Nominal Tyre Pressure: | <b>160 kpa</b>     |
| Section Width:         | <b>485 mm</b>      |
| Outer Diameter:        | <b>1250 mm</b>     |
| Static Loaded Radius:  | <b>570 mm</b>      |
| Rolling Circumference: | <b>3735 mm</b>     |
| SRI:                   | <b>600</b>         |
| Tread depth:           | <b>42 mm</b>       |

| Speed<br>(km/h) | Pressure (bar) |      |      |      |      |      |      |      |
|-----------------|----------------|------|------|------|------|------|------|------|
|                 | 0,60           | 0,80 | 1,00 | 1,20 | 1,40 | 1,60 | 1,80 | 2,00 |
| 10L             | 1720           | 1950 | 2190 | 2425 | 2660 | 2850 | 3005 | 3190 |
| 10H             | 1425           | 1655 | 1880 | 2075 | 2240 | 2370 |      |      |
| 25              | 1470           | 1705 | 1940 | 2140 | 2310 | 2440 |      |      |
| 30              | 1425           | 1655 | 1880 | 2075 | 2240 | 2370 |      |      |
| 40              |                | 1575 | 1790 | 1975 | 2135 | 2255 |      |      |
| 50              |                | 1510 | 1720 | 1895 | 2045 | 2165 |      |      |
| 65              |                |      | 1635 | 1805 | 1950 | 2060 |      |      |
| 70              |                |      | 1490 | 1640 | 1775 | 1875 |      |      |

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

**VREDESTEIN**  
TYRES