

540/65 R 34 145D TL TRAXION 65

EAN CODE: **8714692360541**
SKU CODE: **LB54653445DT6LA00**
ECE NUMBER: **E4-106R-003348**



Recommended rim width:	DW16L
Permitted rim width:	W16L/(D)W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	540 mm
Outer Diameter:	1575 mm
Static Loaded Radius:	715 mm
Rolling Circumference:	4695 mm
SRI:	750
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2420	2745	3080	3410	3745	4005	4225	4485
10H	2005	2330	2645	2920	3150	3335		
25	2070	2400	2725	3010	3245	3435		
30	2005	2330	2645	2920	3150	3335		
40		2220	2520	2780	3000	3175		
50		2125	2415	2665	2875	3045		
65			2300	2540	2740	2900		
70			2095	2310	2495	2640		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.