

600/65 R 34 151D TL TRAXION 65

EAN CODE: **8714692360565**
 SKU CODE: **LB60653451DT6LA00**
 ECE NUMBER: **E4-106R-003350**



Recommended rim width:	DW18L
Permitted rim width:	W18L/DW20B
Nominal Tyre Pressure:	160 kpa
Section Width:	595 mm
Outer Diameter:	1640 mm
Static Loaded Radius:	740 mm
Rolling Circumference:	4905 mm
SRI:	775
Tread depth:	53 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2845	3225	3620	4005	4400	4710	4970	5275
10H	2360	2735	3110	3430	3705	3965		
25	2430	2820	3205	3535	3815	4090		
30	2360	2735	3110	3430	3705	3965		
40		2605	2960	3265	3525	3780		
50		2500	2840	3135	3380	3625		
65			2705	2985	3220	3450		
70			2460	2715	2930	3140		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.