

650/65 R 38 157D TL TRAXION 65

EAN CODE: **8714692360596**
SKU CODE: **LB65653857DT6LA00**
ECE NUMBER: **E4-106R-003353**



Recommended rim width:	DW20B
Permitted rim width:	DW21B
Nominal Tyre Pressure:	160 kpa
Section Width:	650 mm
Outer Diameter:	1840 mm
Static Loaded Radius:	830 mm
Rolling Circumference:	5480 mm
SRI:	875
Tread depth:	55 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	3385	3840	4310	4770	5240	5605	5915	6280
10H	2810	3260	3705	4085	4410	4745		
25	2895	3360	3815	4210	4545	4890		
30	2810	3260	3705	4085	4410	4745		
40		3105	3525	3890	4200	4515		
50		2975	3380	3730	4025	4330		
65			3220	3550	3835	4125		
70			2930	3235	3490	3755		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.