

650/65 R 42 158D TL TRAXION 65

EAN CODE: **8714692360602**

SKU CODE: **LB65654258DT6LA00**

ECE NUMBER: **E4-106R-003336**



Recommended rim width:	DW20B
Permitted rim width:	DW21B
Nominal Tyre Pressure:	160 kpa
Section Width:	650 mm
Outer Diameter:	1925 mm
Static Loaded Radius:	880 mm
Rolling Circumference:	5740 mm
SRI:	925
Tread depth:	55 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	3550	4025	4520	5000	5490	5875	6200	6580
10H	2945	3415	3885	4280	4620	4890		
25	3035	3520	4000	4415	4765	5035		
30	2945	3415	3885	4280	4620	4890		
40		3255	3695	4075	4400	4655		
50		3120	3545	3910	4220	4465		
65			3375	3725	4020	4250		
70			3070	3390	3655	3870		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.