

240/70 R 16 104D TL TRAXION 70

EAN CODE: **8714692344602**
 SKU CODE: **LB24701604DT7LA00**
 ECE NUMBER: **E4-106R-003302**



Recommended rim width:	W8
Permitted rim width:	W8L/W9
Nominal Tyre Pressure:	240 kpa
Section Width:	245 mm
Outer Diameter:	735 mm
Static Loaded Radius:	335 mm
Rolling Circumference:	2190 mm
SRI:	350
Tread depth:	29 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	550	625	705	780	855	915	970	1040	1120	1200	1270	1350
10H	460	530	605	675	725	770	840	910	970	1035		
25	470	550	625	695	750	795	870	940	1000	1065		
30	460	530	605	675	725	770	840	910	970	1035		
40		505	575	645	690	735	800	870	920	985		
50		485	550	620	665	705	770	835	885	945		
65			525	590	630	670	730	795	840	900		
70			480	535	575	610	665	720	765	820		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.