

260/70 R 16 109D TL TRAXION 70

EAN CODE: **8714692344619**
 SKU CODE: **LB26701609DT7LA00**
 ECE NUMBER: **E4-106R-003296**



Recommended rim width:	W8
Permitted rim width:	W8L/W9
Nominal Tyre Pressure:	240 kpa
Section Width:	260 mm
Outer Diameter:	765 mm
Static Loaded Radius:	345 mm
Rolling Circumference:	2280 mm
SRI:	370
Tread depth:	31 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	630	715	805	890	980	1050	1110	1190	1285	1375	1450	1545
10H	525	610	690	775	830	890	965	1045	1110	1185		
25	540	625	715	800	855	920	995	1075	1140	1220		
30	525	610	690	775	830	890	965	1045	1110	1185		
40		580	660	735	790	850	915	995	1055	1130		
50		555	630	705	760	815	880	955	1010	1080		
65			600	675	725	775	840	905	965	1030		
70			545	610	660	705	760	825	875	935		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.