

280/70 R 16 112D TL TRAXION 70

EAN CODE: **8714692344633**
 SKU CODE: **LB28701612DT7LA00**
 ECE NUMBER: **E4-106R-003297**



Recommended rim width:	W9
Permitted rim width:	W8/W8L/W10
Nominal Tyre Pressure:	240 kpa
Section Width:	280 mm
Outer Diameter:	800 mm
Static Loaded Radius:	365 mm
Rolling Circumference:	2390 mm
SRI:	390
Tread depth:	33 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	700	795	890	985	1085	1160	1230	1315	1420	1525	1610	1680
10H	580	675	765	860	920	975	1065	1155	1225	1290		
25	600	695	790	885	950	1005	1100	1190	1265	1325		
30	580	675	765	860	920	975	1065	1155	1225	1290		
40		640	730	815	875	930	1015	1100	1170	1225		
50		615	700	785	840	895	975	1055	1120	1175		
65			665	745	800	850	930	1005	1065	1120		
70			605	680	730	775	845	915	970	1020		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.