

380/70 R 24 125D TL TRAXION 70

EAN CODE: **8714692360701**
 SKU CODE: **LB38702425DT7LA00**
 ECE NUMBER: **E4-106R-004047**



Recommended rim width:	W12
Permitted rim width:	W11/W12L/ (D)W13(L)
Nominal Tyre Pressure:	160 kpa
Section Width:	385 mm
Outer Diameter:	1185 mm
Static Loaded Radius:	540 mm
Rolling Circumference:	3495 mm
SRI:	575
Tread depth:	44 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1350	1530	1720	1905	2090	2240	2370	2510
10H	1120	1300	1480	1655	1775	1895		
25	1155	1340	1525	1705	1830	1955		
30	1120	1300	1480	1655	1775	1895		
40		1240	1405	1575	1690	1805		
50		1185	1350	1510	1620	1735		
65			1285	1440	1545	1650		
70			1170	1310	1405	1500		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.