

420/70 R 24 130D TL TRAXION 70

EAN CODE: **8714692360718**
SKU CODE: **LB42702430DT7LA00**
ECE NUMBER: **E4-106R-004048**



Recommended rim width:	W13
Permitted rim width:	W12(L)/DW13(L)/ (D)W14L
Nominal Tyre Pressure:	160 kpa
Section Width:	430 mm
Outer Diameter:	1240 mm
Static Loaded Radius:	560 mm
Rolling Circumference:	3675 mm
SRI:	600
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1575	1790	2005	2220	2440	2615	2765	2930
10H	1305	1515	1725	1930	2075	2185		
25	1345	1565	1775	1990	2135	2250		
30	1305	1515	1725	1930	2075	2185		
40		1445	1640	1840	1975	2080		
50		1385	1575	1760	1895	1995		
65			1500	1680	1800	1900		
70			1365	1525	1640	1730		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES