

420/70 R 28 133D TL TRAXION 70

EAN CODE: **8714692360749**
 SKU CODE: **LB42702833DT7LA00**
 ECE NUMBER: **E4-106R-004076**



Recommended rim width:	W13
Permitted rim width:	W12(L)/(D)W14L
Nominal Tyre Pressure:	160 kpa
Section Width:	430 mm
Outer Diameter:	1345 mm
Static Loaded Radius:	615 mm
Rolling Circumference:	3975 mm
SRI:	650
Tread depth:	46 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1690	1920	2155	2385	2620	2805	2965	3145
10H	1405	1630	1850	2070	2225	2370		
25	1445	1680	1910	2135	2295	2440		
30	1405	1630	1850	2070	2225	2370		
40		1550	1765	1975	2120	2255		
50		1485	1690	1890	2030	2165		
65			1610	1800	1935	2060		
70			1465	1640	1760	1875		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.