

480/70 R 24 138D TL TRAXION 70

EAN CODE: **8714692360725**
SKU CODE: **LB48702438DT7LA00**
ECE NUMBER: **E4-106R-004049**



Recommended rim width:	DW15L
Permitted rim width:	(D)W14L/W15L/ (D)W16L
Nominal Tyre Pressure:	160 kpa
Section Width:	490 mm
Outer Diameter:	1305 mm
Static Loaded Radius:	585 mm
Rolling Circumference:	3850 mm
SRI:	625
Tread depth:	48 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1940	2200	2470	2735	3005	3220	3405	3605
10H	1610	1870	2125	2375	2555	2715		
25	1660	1925	2190	2450	2630	2795		
30	1610	1870	2125	2375	2555	2715		
40		1780	2020	2265	2430	2585		
50		1705	1940	2170	2330	2480		
65			1845	2065	2220	2360		
70			1680	1880	2020	2150		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES