

# 480/70 R 30 141D TL TRAXION 70

EAN CODE: **8714692360763**  
SKU CODE: **LB48703041DT7LA00**  
ECE NUMBER: **E4-106R-004078**



|                        |                                  |
|------------------------|----------------------------------|
| Recommended rim width: | <b>DW15L</b>                     |
| Permitted rim width:   | <b>(D)W14L/W15L/<br/>(D)W16L</b> |
| Nominal Tyre Pressure: | <b>160 kpa</b>                   |
| Section Width:         | <b>490 mm</b>                    |
| Outer Diameter:        | <b>1470 mm</b>                   |
| Static Loaded Radius:  | <b>665 mm</b>                    |
| Rolling Circumference: | <b>4370 mm</b>                   |
| SRI:                   | <b>700</b>                       |
| Tread depth:           | <b>48 mm</b>                     |

| Speed<br>(km/h) | Pressure (bar) |      |      |      |      |      |      |      |
|-----------------|----------------|------|------|------|------|------|------|------|
|                 | 0,60           | 0,80 | 1,00 | 1,20 | 1,40 | 1,60 | 1,80 | 2,00 |
| 10L             | 2145           | 2435 | 2730 | 3020 | 3320 | 3555 | 3760 | 3985 |
| 10H             | 1780           | 2065 | 2345 | 2625 | 2820 | 2960 |      |      |
| 25              | 1835           | 2125 | 2420 | 2705 | 2905 | 3050 |      |      |
| 30              | 1780           | 2065 | 2345 | 2625 | 2820 | 2960 |      |      |
| 40              |                | 1965 | 2235 | 2500 | 2685 | 2820 |      |      |
| 50              |                | 1885 | 2145 | 2400 | 2575 | 2705 |      |      |
| 65              |                |      | 2040 | 2285 | 2450 | 2575 |      |      |
| 70              |                |      | 1855 | 2080 | 2230 | 2345 |      |      |

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.