

480/70 R 34 143D TL TRAXION 70

EAN CODE: **8714692360770**
SKU CODE: **LB48703443DT7LA00**
ECE NUMBER: **E4-106R-004050**



Recommended rim width:	DW15L
Permitted rim width:	(D)W14L/W15L/ (D)W16L
Nominal Tyre Pressure:	160 kpa
Section Width:	485 mm
Outer Diameter:	1575 mm
Static Loaded Radius:	715 mm
Rolling Circumference:	4645 mm
SRI:	750
Tread depth:	52 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2275	2580	2895	3205	3520	3770	3990	4230
10H	1885	2190	2490	2785	2990	3135		
25	1945	2255	2565	2870	3085	3230		
30	1885	2190	2490	2785	2990	3135		
40		2085	2370	2650	2850	2985		
50		2000	2275	2545	2730	2860		
65			2165	2420	2600	2725		
70			1970	2205	2365	2480		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES