

520/70 R 38 150D TL TRAXION 70

EAN CODE: **8714692360800**
SKU CODE: **LB52703850DT7LA00**
ECE NUMBER: **E4-106R-004080**



Recommended rim width:	DW16L
Permitted rim width:	(D)W15L/W16L/ (D)W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	540 mm
Outer Diameter:	1750 mm
Static Loaded Radius:	790 mm
Rolling Circumference:	5165 mm
SRI:	825
Tread depth:	54 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2750	3120	3500	3875	4255	4560	4820	5110
10H	2280	2645	3010	3365	3615	3850		
25	2350	2725	3100	3470	3725	3970		
30	2280	2645	3010	3365	3615	3850		
40		2520	2865	3205	3445	3670		
50		2415	2745	3075	3300	3520		
65			2615	2930	3145	3350		
70			2380	2665	2860	3050		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES