

480/70 R 28 140D TL TRAXION 70

EAN CODE: **8714692360756**
SKU CODE: **LB48702840DT7LA00**
ECE NUMBER: **E4-106R-004077**



Recommended rim width:	DW15L
Permitted rim width:	(D)W14L/W15L/ (D)W16L
Nominal Tyre Pressure:	160 kpa
Section Width:	495 mm
Outer Diameter:	1405 mm
Static Loaded Radius:	635 mm
Rolling Circumference:	4155 mm
SRI:	675
Tread depth:	48 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2075	2355	2645	2930	3215	3445	3645	3860
10H	1725	2000	2275	2545	2735	2875		
25	1775	2060	2345	2620	2815	2965		
30	1725	2000	2275	2545	2735	2875		
40		1905	2165	2425	2600	2740		
50		1825	2075	2325	2495	2625		
65			1975	2210	2375	2500		
70			1800	2015	2160	2275		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES