

280/85 R 20 118D TL TRAXION 85 II

EAN CODE: **8714692805523**
SKU CODE: **LB288524158T8LA00**
ECE NUMBER:



Alternative size:	11.2 R 24
Recommended rim width:	W10
Permitted rim width:	W9
Nominal Tyre Pressure:	160 kpa
Section Width:	290 mm
Outer Diameter:	1085 mm
Static Loaded Radius:	505 mm
Rolling Circumference:	3220 mm
SRI:	525
Tread depth:	38 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1000	1135	1275	1410	1550	1660	1755	1860
10H	775	895	1020	1140	1225	1300		
25	800	930	1055	1185	1270	1350		
30	775	895	1020	1140	1225	1300		
40		840	955	1065	1145	1215		
50		840	955	1065	1145	1215		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.