

320/85 R 24 122A8/B TL TRAXION 85 II

EAN CODE: **8714692350580**
SKU CODE: **LB348524258T8LA00**
ECE NUMBER: **E4-106R-003317**



Alternative size:	13.6 R 24
Recommended rim width:	W12
Permitted rim width:	W11/W12L
Nominal Tyre Pressure:	160 kpa
Section Width:	360 mm
Outer Diameter:	1195 mm
Static Loaded Radius:	545 mm
Rolling Circumference:	3520 mm
SRI:	575
Tread depth:	43 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1350	1530	1715	1900	2085	2235	2365	2505
10H	1040	1210	1375	1535	1650	1765		
25	1080	1255	1425	1595	1710	1830		
30	1040	1210	1375	1535	1650	1765		
40		1130	1285	1435	1540	1650		
50		1130	1285	1435	1540	1650		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES