

# 420/85 R 34 142A8/B TL TRAXION 85 II

EAN CODE: **8714692350603**  
 SKU CODE: **LB428534428T8LA00**  
 ECE NUMBER: **E4-106R-003318**



Alternative size:	<b>16.9 R 34</b>
Recommended rim width:	<b>DW15L</b>
Permitted rim width:	<b>(D)W13(L)/ (D)W14L/W15L</b>
Nominal Tyre Pressure:	<b>160 kpa</b>
Section Width:	<b>450 mm</b>
Outer Diameter:	<b>1575 mm</b>
Static Loaded Radius:	<b>710 mm</b>
Rolling Circumference:	<b>4650 mm</b>
SRI:	<b>750</b>
Tread depth:	<b>47 mm</b>

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2190	2485	2790	3090	3395	3635	3845	4075
10H	1690	1965	2230	2495	2680	2835		
25	1755	2035	2315	2590	2785	2940		
30	1690	1965	2230	2495	2680	2835		
40		1835	2085	2335	2505	2650		
50		1835	2085	2335	2505	2650		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

**VREDESTEIN**  
TYRES