

# 600/70 R 34 160D TL TRAXION XXL

EAN CODE: **8714692244643**  
 SKU CODE: **LB60703460DTXLA00**  
 ECE NUMBER: **E4-106R-000439**



Recommended rim width:	<b>DW18L</b>
Permitted rim width:	<b>W18L/DW20B</b>
Nominal Tyre Pressure:	<b>240 kpa</b>
Section Width:	<b>610 mm</b>
Outer Diameter:	<b>1700 mm</b>
Static Loaded Radius:	<b>775 mm</b>
Rolling Circumference:	<b>5060 mm</b>
SRI:	<b>800</b>
Tread depth:	<b>53 mm</b>

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	3205	3635	4080	4515	4960	5315	5620	5955	6205	6420	6680	6750
10H	2660	3085	3505	3925	4215	4455	4710	4910	5085	5175		
25	2740	3180	3615	4045	4345	4590	4850	5060	5240	5335		
30	2660	3085	3505	3925	4215	4455	4710	4910	5085	5175		
40		2935	3340	3735	4015	4245	4485	4675	4845	4930		
50		2815	3200	3585	3850	4070	4300	4485	4645	4725		
65			3050	3410	3665	3875	4095	4270	4425	4500		
70			2775	3105	3335	3525	3725	3885	4025	4095		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.