

650/75 R 38 169D TL TRAXION XXL

EAN CODE: **8714692206269**
SKU CODE: **LB65753869DTXLA00**
ECE NUMBER: **E4-106R-000440**



Recommended rim width:	DW23B
Permitted rim width:	DW21B/DW20B
Nominal Tyre Pressure:	240 kpa
Section Width:	695 mm
Outer Diameter:	1935 mm
Static Loaded Radius:	890 mm
Rolling Circumference:	5775 mm
SRI:	925
Tread depth:	54 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	4050	4600	5165	5715	6275	6720	7110	7535	7850	8125	8455	8700
10H	3360	3900	4435	4965	5330	5605	5955	6215	6435	6670		
25	3465	4020	4570	5115	5495	5775	6140	6405	6630	6875		
30	3360	3900	4435	4965	5330	5605	5955	6215	6435	6670		
40		3715	4225	4725	5075	5340	5670	5915	6125	6350		
50		3565	4050	4535	4870	5120	5440	5675	5875	6090		
65			3860	4315	4635	4875	5180	5405	5595	5800		
70			3510	3930	4220	4435	4715	4920	5090	5280		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.