

650/85 R 38 173D TL TRAXION XXL

EAN CODE: **8714692206221**
 SKU CODE: **LB65853873DTXLA00**
 ECE NUMBER: **E4-106R-000441**



Recommended rim width:	DW23B
Permitted rim width:	DW21B/DW20B
Nominal Tyre Pressure:	240 kpa
Section Width:	710 mm
Outer Diameter:	2070 mm
Static Loaded Radius:	940 mm
Rolling Circumference:	6195 mm
SRI:	975
Tread depth:	55 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	4535	5145	5780	6395	7025	7525	7955	8435	8785	9090	9460	9750
10H	3765	4365	4965	5555	5970	6265	6665	6955	7200	7475		
25	3880	4500	5115	5725	6150	6460	6870	7165	7420	7705		
30	3765	4365	4965	5555	5970	6265	6665	6955	7200	7475		
40		4160	4730	5290	5680	5970	6350	6625	6860	7120		
50		3990	4535	5075	5450	5725	6085	6350	6575	6825		
65			4315	4830	5190	5450	5800	6050	6265	6500		
70			3930	4395	4720	4960	5275	5505	5700	5915		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.