

800/70 R 38 178D TL TRAXION XXL

EAN CODE: **8714692206283**
SKU CODE: **LB80703878DTXLA00**
ECE NUMBER: **E4-106R-000442**



Recommended rim width:	DW25B
Permitted rim width:	DW27B
Nominal Tyre Pressure:	240 kpa
Section Width:	825 mm
Outer Diameter:	2065 mm
Static Loaded Radius:	940 mm
Rolling Circumference:	6160 mm
SRI:	975
Tread depth:	58 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10C	5975	6780	7615	8425	9255	9915	10485	11110	11575	11980	12465	12750
10L	5275	5985	6720	7435	8165	8745	9250	9805	10215	10570	11000	11250
10H	4375	5080	5775	6460	6940	7475	7750	8085	8375	8625		
25	4510	5230	5950	6655	7150	7705	7990	8335	8630	8890		
30	4375	5080	5775	6460	6940	7475	7750	8085	8375	8625		
40		4835	5495	6150	6605	7120	7380	7700	7975	8215		
50		4635	5270	5900	6335	6825	7080	7385	7645	7875		
65			5020	5615	6035	6500	6740	7030	7280	7500		
70			4570	5110	5490	5915	6135	6400	6625	6825		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES