

710/75 R 38 174D TL TRAXION XXL

EAN CODE: **8714692291487**
SKU CODE: **LB71753874DTXLA00**
ECE NUMBER: **E4-106R-000534**



Recommended rim width:	DW23B
Permitted rim width:	DW25B
Nominal Tyre Pressure:	240 kpa
Section Width:	715 mm
Outer Diameter:	2000 mm
Static Loaded Radius:	910 mm
Rolling Circumference:	5950 mm
SRI:	950
Tread depth:	57 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10C	5270	5985	6715	7435	8165	8745	9250	9805	10215	10570	11000	11390
10L	4650	5280	5925	6560	7205	7715	8160	8650	9010	9325	9705	10050
10H	3860	4480	5095	5700	6120	6440	6840	7135	7390	7705		
25	3980	4615	5250	5875	6310	6635	7045	7350	7615	7940		
30	3860	4480	5095	5700	6120	6440	6840	7135	7390	7705		
40		4265	4850	5425	5830	6130	6510	6795	7035	7335		
50		4090	4650	5205	5590	5880	6245	6515	6745	7035		
65			4430	4955	5325	5600	5945	6205	6425	6700		
70			4030	4510	4845	5095	5410	5645	5845	6095		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES