

600/65 R 28 154D TL TRAXION XXL

EAN CODE: **8714692326950**
SKU CODE: **LB60652854DTXLA00**
ECE NUMBER: **E4-106R-001098**



Recommended rim width:	DW18L
Permitted rim width:	W18L
Nominal Tyre Pressure:	240 kpa
Section Width:	595 mm
Outer Diameter:	1480 mm
Static Loaded Radius:	670 mm
Rolling Circumference:	4405 mm
SRI:	700
Tread depth:	50 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10L	2610	2960	3320	3675	4035	4320	4555	4835	5045	5280	5510	5625
10H	2165	2510	2855	3145	3395	3620	3835	4025	4195	4315		
25	2230	2585	2940	3245	3500	3735	3955	4150	4325	4445		
30	2165	2510	2855	3145	3395	3620	3835	4025	4195	4315		
40		2390	2715	2995	3235	3450	3655	3835	3995	4105		
50		2290	2605	2875	3100	3310	3505	3675	3830	3940		
65			2480	2735	2955	3150	3335	3500	3650	3750		
70			2260	2490	2690	2865	3035	3185	3320	3415		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES