

900/60 R 38 178 D TL TRAXION XXL

EAN CODE: **8714692309755**
SKU CODE: **LB90603878DTXLA00**
ECE NUMBER: **E4-106R-001090**



Recommended rim width:	DW27B
Permitted rim width:	DW28B/ DW30B
Nominal Tyre Pressure:	240 kpa
Section Width:	870 mm
Outer Diameter:	2040 mm
Static Loaded Radius:	925 mm
Rolling Circumference:	6100 mm
SRI:	975
Tread depth:	60 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10C	5930	6725	7545	8350	9170	9810	10355	10990	11460	11995	12525	12750
10L	5230	5935	6660	7370	8090	8655	9135	9695	10115	10580	11050	11250
10H	4340	5035	5720	6310	6810	7245	7690	8070	8415	8625		
25	4470	5185	5895	6500	7020	7465	7925	8320	8670	8890		
30	4340	5035	5720	6310	6810	7245	7690	8070	8415	8625		
40		4795	5445	6010	6485	6900	7325	7685	8010	8250		
50		4595	5225	5760	6220	6615	7025	7370	7680	7875		
65			4975	5485	5920	6300	6690	7020	7315	7500		
70			4525	4995	5390	5735	6085	6390	6655	6825		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES