

13.0/75 – 16 IMP 135 A8 TL AW

EAN CODE: **8714692263279**
SKU CODE: **LB137516358AWLA00**
ECE NUMBER: **E4-106R-000419**



Recommended rim width:	11.00
Nominal Tyre Pressure:	300 kpa
Section Width:	345 mm
Outer Diameter:	905 mm
Static Loaded Radius:	405 mm
Rolling Circumference:	2725 mm
SRI:	425
Tread depth:	12 mm

Speed (km/h)	Pressure (bar)									
	1,00	1,25	1,50	1,75	2,00	2,25	2,50	2,75	3,00	4,00
	LLV									HLV
10	1630	1860	2070	2260	2450	2620	2790	2950	3100	3680
25	1390	1580	1760	1920	2080	2230	2370	2510	2640	3120
30	1300	1490	1650	1810	1960	2100	2230	2360	2480	2940
40			1480	1620	1750	1870	1990	2110	2220	2620
50				1450	1570	1690	1790	1890	1990	2360

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- LLV (Low Load Variation)
- HLV (High Load Variation)