

12.5/80 – 18 IMP 142 A8 TL AW

EAN CODE: **8714692263262**
SKU CODE: **LB128018428AWLA00**
ECE NUMBER: **E4-106R-000425**



Recommended rim width:	11.00
Nominal Tyre Pressure:	370 kpa
Section Width:	340 mm
Outer Diameter:	975 mm
Static Loaded Radius:	450 mm
Rolling Circumference:	2985 mm
SRI:	475
Tread depth:	11 mm

Speed (km/h)	Pressure (bar)							
	1,00	1,50	2,00	2,50	3,00	3,50	3,75	5,00
	LLV							HLV
10	1760	2230	2640	3000	3340	3660	3820	4520
25	1500	1900	2240	2560	2840	3120	3240	3840
30	1410	1780	2110	2410	2680	2930	3060	3600
40		1590	1890	2150	2390	2620	2720	3220
50			1700	1930	2150	2350	2450	2900

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- LLV (Low Load Variation)
- HLV (High Load Variation)