280/85 R 28 118A8/B TL TRAXION 85 II

EAN CODE: **8714692350573**

SKU CODE: **LB288528188T8LA00**

ECE NUMBER: **E4-106R-003321**

Alternative size:	11.2 R 28	
Recommended rim width:	W10	
Permitted rim width:	W9	
Nominal Tyre Pressure:	160	kpa
Section Width:	280	mm
Outer Diameter:	1195	mm
Static Loaded Radius:	555	mm
Rolling Circumference:	3545	mm
SRI:	575	
Tread depth:	38	mm



Speed	Pressure (bar)								
(km/h)	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	
10L	1080	1225	1375	1520	1670	1790	1895	2005	
10H	835	965	1100	1230	1320	1410			
25	865	1005	1140	1275	1370	1465			
30	835	965	1100	1230	1320	1410			
40		905	1025	1150	1235	1320			
50		905	1025	1150	1235	1320			

- · The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- · For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- · 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

