

320/85 R 28 124A8/B TL TRAXION 85 II

EAN CODE: **8714692344725**
SKU CODE: **LB328528248T8LA00**
ECE NUMBER: **E4-106R-002517**



Alternative size:	12.4 R 28
Recommended rim width:	W11
Permitted rim width:	W9/(D)W10
Nominal Tyre Pressure:	160 kpa
Section Width:	330 mm
Outer Diameter:	1250 mm
Static Loaded Radius:	575 mm
Rolling Circumference:	3700 mm
SRI:	600
Tread depth:	41 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1320	1500	1680	1860	2045	2190	2315	2455
10H	1020	1185	1345	1505	1615	1710		
25	1055	1225	1395	1560	1675	1775		
30	1020	1185	1345	1505	1615	1710		
40		1105	1255	1405	1510	1600		
50		1105	1255	1405	1510	1600		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES