

340/85 R 38 133A8/B TL TRAXION 85 II

EAN CODE: **8714692623745**
 SKU CODE: **LB348538338T8LA00**
 ECE NUMBER: **E4-106R-004083**



Alternative size:	13.6 R 38
Recommended rim width:	W12
Permitted rim width:	W11/DW12
Nominal Tyre Pressure:	160 kpa
Section Width:	355 mm
Outer Diameter:	1555 mm
Static Loaded Radius:	705 mm
Rolling Circumference:	4620 mm
SRI:	750
Tread depth:	43 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1685	1910	2145	2375	2605	2790	2955	3130
10H	1300	1510	1715	1920	2060	2205		
25	1350	1565	1780	1990	2140	2285		
30	1300	1510	1715	1920	2060	2205		
40		1410	1600	1795	1925	2060		
50		1410	1600	1795	1925	2060		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.