

# 380/85 R 28 133A8/B TL TRAXION 85 II

EAN CODE: **8714692344770**  
 SKU CODE: **LB388528338T8LA00**  
 ECE NUMBER: **E4-106R-002510**



Alternative size:	<b>14.9 R 28</b>
Recommended rim width:	<b>W13</b>
Permitted rim width:	<b>W11/ W12(L)/ DW13(L)</b>
Nominal Tyre Pressure:	<b>160 kpa</b>
Section Width:	<b>400 mm</b>
Outer Diameter:	<b>1350 mm</b>
Static Loaded Radius:	<b>610 mm</b>
Rolling Circumference:	<b>3980 mm</b>
SRI:	<b>650</b>
Tread depth:	<b>44 mm</b>

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1715	1950	2185	2420	2660	2850	3010	3190
10H	1325	1540	1750	1955	2100	2205		
25	1375	1595	1815	2030	2180	2285		
30	1325	1540	1750	1955	2100	2205		
40		1440	1635	1830	1965	2060		
50		1440	1635	1830	1965	2060		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.