

420/85 R 24 137A8/B TL TRAXION 85 II

EAN CODE: **8714692344800**
 SKU CODE: **LB428524378T8LA00**
 ECE NUMBER: **E4-106R-002511**



Alternative size:	16.9 R 24
Recommended rim width:	DW15L
Permitted rim width:	(D)W13(L)/(D) W14L/W15L
Nominal Tyre Pressure:	160 kpa
Section Width:	450 mm
Outer Diameter:	1315 mm
Static Loaded Radius:	590 mm
Rolling Circumference:	3850 mm
SRI:	625
Tread depth:	47 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	1875	2130	2390	2645	2905	3110	3290	3485
10H	1450	1680	1910	2140	2295	2460		
25	1500	1745	1980	2220	2380	2555		
30	1450	1680	1910	2140	2295	2460		
40		1570	1785	2000	2145	2300		
50		1570	1785	2000	2145	2300		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.