

460/85 R 34 147A8/B TL TRAXION 85 II

EAN CODE: **8714692350627**
SKU CODE: **LB468534478T8LA00**
ECE NUMBER: **E4-106R-003320**



Alternative size:	18.4 R 34
Recommended rim width:	DW16L
Permitted rim width:	(D)W14L/(D) W15L/W16L
Nominal Tyre Pressure:	160 kpa
Section Width:	490 mm
Outer Diameter:	1645 mm
Static Loaded Radius:	740 mm
Rolling Circumference:	4855 mm
SRI:	775
Tread depth:	49 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2520	2860	3210	3550	3900	4180	4420	4685
10H	1945	2255	2565	2870	3085	3290		
25	2020	2340	2660	2980	3200	3415		
30	1945	2255	2565	2870	3085	3290		
40		2110	2400	2685	2885	3075		
50		2110	2400	2685	2885	3075		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES