

460/85 R 38 149A8/B TL TRAXION 85 II

EAN CODE: **8714692623776**
 SKU CODE: **LB468538498T8LA00**
 ECE NUMBER: **E4-106R-004085**



Alternative size:	18.4 R 38
Recommended rim width:	DW16L
Permitted rim width:	(D)W14L/(D) W15L/W16L
Nominal Tyre Pressure:	160 kpa
Section Width:	490 mm
Outer Diameter:	1755 mm
Static Loaded Radius:	790 mm
Rolling Circumference:	5195 mm
SRI:	825
Tread depth:	49 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2655	3010	3380	3740	4110	4400	4655	4935
10H	2050	2380	2705	3025	3250	3480		
25	2125	2465	2805	3140	3370	3610		
30	2050	2380	2705	3025	3250	3480		
40		2220	2525	2825	3035	3250		
50		2220	2525	2825	3035	3250		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.