

480/70 R 38 145D TL TRAXION 70

EAN CODE: **8714692360794**
 SKU CODE: **LB48703845DT7LA00**
 ECE NUMBER: **E4-106R-004079**



Recommended rim width:	DW15L
Permitted rim width:	(D)W14L/W15L/ (D)W16L
Nominal Tyre Pressure:	160 kpa
Section Width:	485 mm
Outer Diameter:	1685 mm
Static Loaded Radius:	765 mm
Rolling Circumference:	5015 mm
SRI:	800
Tread depth:	52 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2400	2725	3060	3385	3720	3980	4210	4465
10H	1990	2310	2630	2940	3160	3335		
25	2050	2380	2710	3030	3255	3435		
30	1990	2310	2630	2940	3160	3335		
40		2200	2500	2800	3005	3175		
50		2110	2400	2685	2885	3045		
65			2285	2555	2745	2900		
70			2080	2325	2500	2640		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.