

# VF 850/50 R 30.5 IMP 188D TL FLOTATION OPTIMALL



EAN CODE: **8714692999864**  
SKU CODE: **LB85503088DFOLA00**  
ECE NUMBER: **E4-106R-005057**

Recommended rim width:	<b>AG 28.00</b>
Nominal Tyre Pressure:	<b>320 kpa</b>
Section Width:	<b>860 mm</b>
Outer Diameter:	<b>1650 mm</b>
Static Loaded Radius:	<b>720 mm</b>
Rolling Circumference:	<b>4980 mm</b>
SRI:	<b>775</b>
Tread depth:	<b>28 mm</b>

Speed (km/h)	Pressure (bar)						
	0,80	1,20	1,60	2,00	2,40	2,80	3,20
10	6515	8380	10145	11370	13120	14865	16400
25	5800	7460	9035	10120	11680	13235	14600
30	5605	7205	8725	9775	11280	12780	14100
40	5125	6590	7980	8940	10320	11695	12900
50	4650	5975	7240	8110	9360	10605	11700
65	3975	5110	6185	6930	8000	9065	10000
70	3615	4650	5630	6310	7280	8250	9100

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.