

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name/Description of battery

Li-ion Battery

1a. Name/Description of the cells inside the battery

Li-ion Battery

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacturer of battery

Name	Roofer Energy Technology (Baoshan) Co., Ltd.
Address	Luhua Industrial Park, Baoshan Industrial and Trade Zone, Hanzhuang town, Longyang district, Baoshan, Yunnan Province
Phone	13502883088
Email	info@rooferbs.com
Website	www.rooferbs.com

2a. Manufacturer of the equipment (if the battery is contained in equipment)

Name	Jiangsu Yoen Electric Technology Co., Ltd.
Address	No.99 Taihu Road, Yancheng, Jiangsu, China
Phone	86-515-88301122
Email	info@yoentools.com
Website	www.yoentools.com

3. Test laboratory of battery

Name	Shanghai Research Institute of Chemical Industry Testing Co., Ltd.
Address	No. 345 East Yunling Road, Shanghai
Phone	+86-21-31765555
Email	zmh@ghs.cn
Website	www.ghs.cn

4. ID-number and date

Unique test report identification number	1120040267	Date of test report	2020-5-20
--	------------	---------------------	-----------

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Li-ion Battery

DESCRIPTION OF BATTERY

5. Mark the type of battery with an "e"

<input checked="" type="radio"/>	Lithium ion battery		
<input type="radio"/>	Lithium hybrid battery		
		Lithium metal battery	<input type="radio"/>

6. Parameters

Mass in gram (g):	
Lithium ion: Indicate watt-hour rating (Wh):	46
Lithium metal: Indicate lithium metal content in gram (g):	9.25
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):	g Wh

7. Physical description of battery

Blue Cylinder plastics film shell

8. Model numbers

INR18650-2500mAh

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "e"

	N/A	pass	fail
T1 - Altitude simulation	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T2 - Thermal Test	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T3 - Vibration	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T4 - Shock	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T5 - External Short Circuit	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T7 - Overcharge	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Li-ion Battery

9a. UN 38.3 Test Confirmation for the Cells inside the battery

When no separate document for the cells is provided, this confirms that the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as „passed“ and here under 9.a. „Cell UN 38.3 Test confirmed“ needs to be ticked.



Cell
UN 38.3 Test
confirmed

Cell
UN 38.3 Test
NOT
confirmed



10. Reference to assembled battery testing requirements

N/A

11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto

ST/SG/AC.10/11/Rev.6/Amend.1 UN38.3 UNITED NATIONS

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing batteries

Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?



YES

NO



13. Are the following parameters exceeded?

Lithium ion battery: more than 100 Wh

Lithium metal battery: more than 2 g Lithium

Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh



YES

NO



Check point 14 – 16 need to be answered when 13 has been ticked "YES".

14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?



YES

NO



15. Is each battery equipped with an effective means of preventing external short circuits?



YES

NO



16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?



N/A



YES

NO



17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batteries and lithium polymer batteries

State of Charge (SoC) max. 30 %



N/A



YES

NO



IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

Li-ion Battery

18.a) Only button cells enclosed?

18.b) Number of enclosed batteries per equipment

18.c) Confirmation that no dangerous amount of

18.d) Confirmation that the equipment will not overheat during transport e.g. da

18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160

20. Title, Surname, First name

21. Company stamp and signature

Yancheng, 2024.3.25

Manager, Jack Jiang

稿子更

