

# FLOTATION

- Landwirtschaft
- Anhänger
- Vorurteil



(Reduzierte Verdichtung) Größeres  
Volumen, Größere Stellfläche

(Gerundete Schulter)  
Reduzierte Bodenstörung.

Size	Rim
700/50-22.5	AG24.00
600/55-22.5	AG20.00
560/60-22.5	AG16.00
500/50-17	16.00 DC
480/45-17	16.00 DC
480/45-17	16.00 DC
480/45-17	16.00 DC
480/45-17	16.00 DC

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Free Rolling
		in	in						40
								25	
700/50-22.5	AG24.00	705	1270	572	3810		174 A8	2.4	6700
		27.8	50.0	23	150		162 A8	35	14760

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Free Rolling
		in	in						40
								25	
600/55-22.5	AG20.00	605	1240	560	3720		165 A8	2.6	5150
		23.8	48.8	22	147		153 A8	38	11340

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Free Rolling
		in	in						40
								25	
560/60-22.5	AG16.00	555	1240	560	3720		167 A8	2.8	5450
		21.9	48.8	22	147		155 A8	41	12000

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
mm	mm	bar	in	mm	in	mm	in	mm
in	in	psi	500/50-17	16.00 DC	500	950	444.6	2850
				19.7	37.4	18	112	

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Free Rolling
		in	in						40
								25	
480/45-17	16.00 DC	490	866	405.3	2598		138 A8	2.3	2360
		19.3	34.1	16	102			33	5200

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		bar	mm	mm	mm	mm		
in	in	psi	480/45-17	16.00 DC	490 19.3	866 34.1	405.3 16	2598 102

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		bar	mm	mm	mm	mm		
in	in	psi	480/45-17/3	16.00 DC	490 19.3	866 34.1	405.3 16	2598 102

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		bar	mm	mm	mm	mm		
in	in	psi	480/45-17/4	16.00 DC	490 19.3	866 34.1	405.3 16	2598 102