

FLOTATION

- Landwirtschaft
- Anhänger
- Vorurteil



(Größeres Volumen und Fläche)
Reduzierte Verdichtung

(Hohe Traglast) Robustes
Nylongehäuse, Starke
Wulstbündel

(Abgerundete Schulter)
Reduzierte Bodenstörung

(Größeres Volumen und
Fläche) Verringerte
Verdichtung

Size	Rim
400/55-17.5	AG11.75
400/55-22.5	13.00DC
500/50-17	16.00DC
500/50-17	16.00DC
500/50-22.5	AG16.00
500/60-22.5	16.00DC
550/45-22.5	16.00 DC
550/45-22.5	16.00 DC
550/60-22.5	16.00 DC
550/60-22.5	16.00 DC
600/50-22.5	20.00DC
600/55-22.5	AG20.00
700/40-22.5	24.00DC
700/40-22.5	24.00DC
700/50-22.5	AG24.00

700/50-26.5	24.00DC
800/45-26.5	28.00DC
800/45-26.5	28.00DC

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)	
									Speed,km/h(mph)	
		Free Rolling								
		mm	mm						mm	mm
in	in	in	in	in	in	psi	25	31		
400/55-17.5	AG11.75	887	375	420	2730.860		152 A8	4.6	3550	3150
		34.9	14.8	17	83	108	148 B	67	7820	6940
							139 A8			
							135 B			

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)	
									Speed,km/h(mph)	
		Free Rolling								
		mm	mm						mm	mm
in	in	in	in	in	in	psi	25	31		
400/55-22.5	13.00DC	1060	375	494	3263.486		152 A8	4.0	3550	3250
		41.7	14.8	19	449	129	149 B	58	7820	7160
							140 A8			
							136 B			

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)	
									Speed,km/h(mph)	
		Free Rolling								
		mm	mm						mm	mm
in	in	in	in	in	in	psi	25	31		
500/50-17	16.00DC	500	945	415	2752		143 A8	3.2	3550	
		19.7	37.2	16.3	108			46	7820	

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)	
									Speed,km/h(mph)	
		Free Rolling								
		mm	mm						mm	mm
in	in	in	in	in	in	psi	25	31		
500/50-17	16.00DC	500	945	415	2752		152 A8	4.0	4125	
		19.7	37.2	16.3	108			58	9090	

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)	
									Speed,km/h(mph)	
		Free Rolling								
		mm	mm						mm	mm
in	in	in	in	in	in	psi	25	31		
500/50-22.5	AG16.00	500	1070	487	3210		158 A8	3.0	4250	
		19.7	42.1	19	126		155 B	44	9360	
							146 A8			
							142 B			

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
									Free Rolling
									mm
in	in	in	in	in	in	in	psi	25	
500/60-22.5	16.00DC	500	1170	510	3380		163 A8	3.2	4875
		19.7	46.1	20	133		151 A8 148 B	46	10740

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm					
in	in	psi	in	in	in	in	in	
			550/45-22.5	16.00 DC	1070	550	470	3205
					42.1	21.7	19	126

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm					
in	in	psi	in	in	in	in	in	
			550/45-22.5	16.00 DC	550	1070	470	3205
					21.7	42.1	19	126

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm					
in	in	psi	in	in	in	in	in	
			550/60-22.5	16.00 DC	550	1238	540	3720
					21.7	48.7	21	147

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm					
in	in	psi	in	in	in	in	in	
			550/60-22.5	16.00 DC	550	1238	540	3720
					21.7	48.7	21	147

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
									Free Rolling
									mm
in	in	in	in	in	in	in	psi	25	

600/50-22.5	20.00DC	600 23.6	1170 46.1	510 20	3498 138		165 A8 161 B 153 A8 149 B	2.6	5150
								38	11340

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h(mph)		
									Free Rolling	Drive Wheel	
										mm	mm
		mm	mm	mm	mm	mm	mm	bar	40	bar	40
		in	in	in	in	in	in	psi	25	psi	25
600/55-22.5	AG20.00	605 23.8	1240 48.8	560 22	3720 147		165 A8 153 A8	2.6	5800	2.6	4000
								38	12780	38	8810

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h(mph)		
									Free Rolling	Drive Wheel	
										mm	mm
		mm	mm	mm	mm	mm	mm	bar	40	bar	40
		in	in	in	in	in	in	psi	25	psi	25
600/55-22.5	AG20.00	605 23.8	1240 48.8	560 22	3720 147		165 A8 153 A8	2.6	5800	2.6	4000
								38	12780	38	8810

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h(mph)		
									Free Rolling	Drive Wheel	
										mm	mm
		mm	mm	mm	mm	mm	mm	bar	40	bar	40
		in	in	in	in	in	in	psi	25	psi	25
700/40-22.5	24.00DC	700 27.6	1170 46.1	510 20	3522 139		166 A8 162 B 154 A8 150 B	2.2	5300	2.2	3750
								32	11670	32	8260

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h(mph)		
									Free Rolling	Drive Wheel	
										mm	mm
		mm	mm	mm	mm	mm	mm	bar	40	bar	40
		in	in	in	in	in	in	psi	25	psi	25
700/40-22.5	24.00DC	700 27.6	1170 46.1	510 20	3522 139		173 A8 169 B 160 A8 156 B	3.2	6000	3.2	4500
								46	13220	46	9910

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h(mph)		
									Free Rolling	Drive Wheel	
										mm	mm
		mm	mm	mm	mm	mm	mm	bar	40	bar	40
		in	in	in	in	in	in	psi	25	psi	25
700/50-22.5	AG24.00	705 27.8	1270 50.0	572 23	3810 150		174 A8 162 A8	2.8	6700	2.8	4750
								41	14760	41	10460

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h(mph)		
									Free Rolling	Drive Wheel	
										mm	mm
		mm	mm	mm	mm	mm	mm	bar	40	bar	40

		in	in	in	in	in	in	psi	25	psi	25
700/50-22.5	AG24.00	705	1270	572	3810		174 A8	2.8	6700	2.8	4750
		27.8	50.0	23	150		162 A8	41	14760	41	10460

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
									Speed,km/h(mph)		
		SW	OD						Free Rolling	Drive Wheel	
		mm	mm						40	bar	40
in	in	25	psi	25							
700/50-26.5	24.00DC	700	1333	585	3986		174 A8	2.4	6700	2.4	4750
		27.6	52.5	23	157		170 B	35	14760	35	10460
							162 A8				
							158 B				

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
									Speed,km/h(mph)		
		SW	OD						Free Rolling	Drive Wheel	
		mm	mm						40	bar	40
in	in	25	psi	25							
800/45-26.5	28.00DC	800	1355	585	4016		177 A8	2.2	7300	2.2	5000
		31.5	53.3	23	158		173 B	32	16080	32	11010
							164 A8				
							160 B				

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
									Speed,km/h(mph)		
		SW	OD						Free Rolling	Drive Wheel	
		mm	mm						40	bar	40
in	in	25	psi	25							
800/45-26.5	28.00DC	800	1355	585	4016		170 A8	1.7	6000	1.7	4250
		31.5	53.3	23	158		167 B	25	13220	25	9360
							158 A8				
							155 B				