

# FLOTATION

- Landwirtschaft
- Anhänger
- Bagger

(Gerundete Schulter) Reduzierter Schaden an Pflanzen

(Vorteil) Reduzierte Verdichtung



(MERKMAL) Größeres Volumen und Fläche

Size	Rim
550/60-22.5	16.00 DC
550/60-22.5	16.00 DC
600/50-22.5	20.00DC
600/50-22.5	20.00DC
700/40-22.5	24.00DC
700/40-22.5	24.00DC

Size	RIM	Inflated Tire Dimension
		Inflation Pressure
Recommended load,kg (lbs)	Speed,km/h(mph)	SW
OD		bar
psi	<b>500/60-22.5</b>	

Size	RIM	Inflated Tire Dimension
		Inflation Pressure
Recommended load,kg (lbs)	Speed,km/h(mph)	SW
OD		bar
psi	<b>500/60-22.5</b>	

Size	RIM	Inflated Tire Dimension
		Inflation Pressure
Recommended load,kg (lbs)	Speed,km/h(mph)	SW
OD		bar
psi	<b>500/60-22.5/3</b>	

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm	bar	in	in	in	in
in	in	psi	<b>550/60-22.5</b>	<b>16.00 DC</b>	550 21.7	1238 48.7	540 21	3720 147

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm	bar	in	in	in	in
in	in	psi	<b>550/60-22.5</b>	<b>16.00 DC</b>	550 21.7	1238 48.7	540 21	3720 147

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm	bar	in	in	in	in
in	in	psi	<b>550/60-22.5</b>	<b>16.00 DC</b>	550 21.7	1238 48.7	540 21	3720 147

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
		mm	mm	bar	in	in	in	in
in	in	psi	<b>550/60-22.5</b>	<b>16.00 DC</b>	550 21.7	1238 48.7	540 21	3720 147

Size	RIM	Inflated Tire Dimension
		Inflation Pressure
Recommended load,kg (lbs)	Speed,km/h(mph)	SW
OD		bar

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
mm	mm	bar	mm	in	in	in	in	in
in	in	psi	600/50-22.5	20.00DC	611 24.1	1170 46.1	510 20	3472 137

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h (mph)		
									Free Rolling	Drive Wheel	
									mm	mm	bar
mm	mm	mm	mm	mm	mm	mm	bar	40	bar	40	
in	in	in	in	in	in	in	psi	25	psi	25	
600/50-22.5	20.00DC	611 24.1	1170 46.1	510 20	3472 137		170 A8 166 B 158 A8 154 B	2.9	6000	2.9	4250
								42	13220	42	9360

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
mm	mm	bar	mm	in	in	in	in	in
in	in	psi	700/40-22.5	24.00DC	700 27.6	1170 46.1	510 20	3522 139

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
mm	mm	bar	mm	in	in	in	in	in
in	in	psi	700/40-22.5	24.00DC	700 27.6	1170 46.1	510 20	3522 139

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h (mph)		
									Free Rolling	Drive Wheel	
									mm	mm	bar
mm	mm	mm	mm	mm	mm	mm	bar	40	bar	40	
in	in	in	in	in	in	in	psi	25	psi	25	
700/40-22.5	24.00DC	700 27.6	1170 46.1	510 20	3522 139		173 A8 169 B 160 A8 156 B	3.2	6700	3.2	4750
								46	14760	46	10460

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)		
		SW	OD						Speed,km/h (mph)		
									Free Rolling	Drive Wheel	
									mm	mm	bar
mm	mm	mm	mm	mm	mm	mm	bar	40	bar	40	
in	in	in	in	in	in	in	psi	25	psi	25	

700/40- 22.5	24.00DC	700	1170	510	3522		173 A8	3.2	6700	3.2	4750
		27.6	46.1	20	139		169 B	46	14760	46	10460
							160 A8				
							156 B				