

T422 VALUE

- Landwirtschaft
- Anhänger
- Vorurteil

(Reduzierte Verdichtung) Größeres
Volumen, Größere Stellfläche



(Abgerundete Schulter)
Reduzierte Bodenstörung

Size	Rim
400/55-22.5	13.00DC
400/55-22.5	13.00DC
400/55-22.5	13.00DC
400/55-22.5	13.00DC
400/60-15.5	13
500/45-22.5	14
500/45-22.5	14
500/60-22.5	16.00DC
550/45-22.5	16.00DC
550/60-22.5	16.00DC

in	in	psi	500/45-22.5	14	500 19.7	1045 41.1	470 19	3165 125
----	----	-----	-------------	----	-------------	--------------	-----------	-------------

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
in	in	psi	500/60-22.5	16.00DC	500 19.7	1170 46.1	510 20	3380 133

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
in	in	psi	500/60-22.5	16.00DC	500 19.7	1170 46.1	510 20	3380 133

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
in	in	psi	550/45-22.5	16.00DC	550 21.7	1070 42.1	475 19	3200 126

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure
		Recommended load,kg (lbs)	Speed,km/h (mph)					
		SW	OD					
in	in	psi	550/60-22.5	16.00DC	550 21.7	1244 49.0	541 21	3597 142