

# GM LOADER HD

- Bau & Industrie
- Kompaktlader
- Vorurteil

(Höhere Profiltiefe mit extra dickem Seitenwall) Verbesserte Traktion und Widerstandsfähigkeit gegen Durchstiche

(Speziell gestaltete Felgeschützer) Bessere Schutz des Felgenflansches



(Starke Nylonkarkasse)  
Exzellente Haltbarkeit

Size	Rim
10 - 16.5 HD	8.25
27x10.5-15	8LB

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
10 - 16.5 HD	8.25	264	773	358	2320		121 A8	5.2	1450
		10.4	30.4	14	91			75	3190

Size	RIM	Inflated Tire Dimension		
		Inflation Pressure	Recommended load,kg (lbs)	Speed,km/h(mph)
OD	Constant Load	bar	40	
psi	25			
5.5	1850	12 - 16.5 HD		
80	4070			

Size	RIM	Inflated Tire Dimension		
		Inflation Pressure	Recommended load,kg (lbs)	Speed,km/h(mph)
OD	Constant Load	bar	40	
psi	25			
5.5	2000	12 - 16.5 HD		
80	4410			

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
27x10.5-15	8LB	259	691	330	2110		105 A8	4.2	925
		10.2	27.2	13	83			61	2040

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
27x10.5-15	8LB	259	691	330	2110		105 A8	4.2	925
		10.2	27.2	13	83			61	2040