

MPT 808

- Bau & Industrie
- MPT
- Vorurteil

(Starkes Nylongehäuse) Höhere Festigkeit und Stabilität

(Speziell entwickelte breite Laschen) Bessere Selbstreinigung



(Überlegene Laufflächenmischung) Reiß- und Rissfestigkeit

| Size | Rim |
|--------------------------|-----|
| 10.0/75-15.3 | 9 |
| 10.5-18 | 9 |
| 10.5-20 | 9 |
| 11.5/80-15.3 | 9 |
| 12.0/75-18 / (300/75-18) | W9 |
| 12.0-18 | W9 |
| 12.5-18 | 11 |
| 12.5-20 | 11 |
| 14.5-20 | 11 |
| 18-19.5 | 11 |
| 405/70-20 IND | 13 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) | | |
|--------------|-----|-------------------------|------|-----|------|----|--------|--------------------|---------------------------|-------------|------|
| | | | | | | | | | Speed,km/h(mph) | | |
| | | SW | OD | | | | | | Free Rolling | Drive Wheel | |
| | | mm | mm | | | | | | | 40 | bar |
| in | in | 25 | psi | 25 | | | | | | | |
| 10.0/75-15.3 | 9 | 260 | 775 | 365 | 2400 | | 130 A8 | 5.5 | 1900 | 5.5 | 1320 |
| | | 10.2 | 30.5 | 14 | 95 | | 118 A8 | 80 | 4190 | 80 | 2910 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommende load,kg (lbs) | |
|---------|-----|-------------------------|------|-----|------|----|-------|--------------------|--------------------------|------|
| | | | | | | | | | Speed,km/h(mph) | |
| | | SW | OD | | | | | | Constant Load | |
| | | mm | mm | | | | | | 50 | |
| in | in | 31 | | | | | | | | |
| 10.5-18 | 9 | 270 | 905 | 400 | 2690 | | | 134 B | 4.5 | 2120 |
| | | 10.6 | 35.6 | 16 | 106 | | | | 65 | 4670 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommende load,kg (lbs) | |
|---------|-----|-------------------------|------|-----|------|----|-------|--------------------|--------------------------|------|
| | | | | | | | | | Speed,km/h(mph) | |
| | | SW | OD | | | | | | Constant Load | |
| | | mm | mm | | | | | | 50 | |
| in | in | 31 | | | | | | | | |
| 10.5-20 | 9 | 270 | 955 | 445 | 2880 | | | 135 B | 4.3 | 2180 |
| | | 10.6 | 37.6 | 18 | 113 | | | | 62 | 4800 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) | | |
|--------------|-----|-------------------------|------|-----|------|----|--------|--------------------|---------------------------|-------------|------|
| | | | | | | | | | Speed,km/h(mph) | | |
| | | SW | OD | | | | | | Free Rolling | Drive Wheel | |
| | | mm | mm | | | | | | | 40 | bar |
| in | in | 25 | psi | 25 | | | | | | | |
| 11.5/80-15.3 | 9 | 292 | 870 | 395 | 2580 | | 139 A8 | 4.8 | 2430 | 4.8 | 1700 |
| | | 11.5 | 34.3 | 16 | 102 | | 126 A8 | 69 | 5350 | 69 | 3740 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) | | |
|--------------------------|-----|-------------------------|------|-----|------|----|--------|--------------------|---------------------------|-------------|------|
| | | | | | | | | | Speed,km/h(mph) | | |
| | | SW | OD | | | | | | Free Rolling | Drive Wheel | |
| | | mm | mm | | | | | | | 40 | bar |
| in | in | 25 | psi | 25 | | | | | | | |
| 12.0/75-18 / (300/75-18) | W9 | 295 | 915 | 427 | 2755 | | 139 A8 | 4.0 | 2430 | 4.0 | 1700 |
| | | 11.6 | 36.0 | 17 | 109 | | 126 A8 | 58 | 5350 | 58 | 3740 |

| Size | RIM | Inflated Tire Dimension | SLR | RC | PR | LI/SS | Inflation Pressure | Recommende load,kg (lbs) |
|------|-----|-------------------------|-----|----|----|-------|--------------------|--------------------------|
| | | | | | | | | Speed,km/h(mph) |

| | | SW | OD | | | | | | Constant Load |
|---------|----|------|------|-----|------|----|--------|-----|---------------|
| | | mm | mm | mm | mm | mm | mm | bar | 30 |
| | | in | in | in | in | in | in | psi | 19 |
| 12.0-18 | W9 | 295 | 930 | 430 | 2775 | | 145 A6 | 4.5 | 2900 |
| | | 11.6 | 36.6 | 17 | 109 | | | 65 | 6390 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) |
|---------|-----|-------------------------|------|-----|------|----|-------|--------------------|---------------------------|
| | | SW | OD | | | | | | Speed,km/h(mph) |
| | | mm | mm | | | | | | Constant Load |
| | | in | in | | | | | | mm |
| 12.5-18 | 11 | 325 | 990 | 450 | 2940 | | 135 B | 3.5 | 2180 |
| | | 12.8 | 39.0 | 18 | 116 | | | 51 | 4800 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) |
|---------|-----|-------------------------|------|-----|------|----|-------|--------------------|---------------------------|
| | | SW | OD | | | | | | Speed,km/h(mph) |
| | | mm | mm | | | | | | Constant Load |
| | | in | in | | | | | | mm |
| 12.5-20 | 11 | 325 | 1042 | 480 | 3065 | | 135 D | 4.0 | 2500 |
| | | 12.8 | 41.0 | 19 | 121 | | | 58 | 5510 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) |
|---------|-----|-------------------------|------|-----|------|----|-------|--------------------|---------------------------|
| | | SW | OD | | | | | | Speed,km/h(mph) |
| | | mm | mm | | | | | | Constant Load |
| | | in | in | | | | | | mm |
| 14.5-20 | 11 | 355 | 1098 | 505 | 3260 | | 143 B | 3.5 | 2725 |
| | | 14.0 | 43.2 | 20 | 128 | | | 51 | 6000 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommended load,kg (lbs) |
|---------|-----|-------------------------|------|-----|------|----|-------|--------------------|---------------------------|
| | | SW | OD | | | | | | Speed,km/h(mph) |
| | | mm | mm | | | | | | Constant Load |
| | | in | in | | | | | | mm |
| 18-19.5 | 11 | 457 | 1110 | 503 | 3227 | | 165 B | 7.3 | 5150 |
| | | 18.0 | 43.7 | 20 | 127 | | | 105 | 11340 |

| Size | RIM | Inflated Tire Dimension | | SLR | RC | PR | LI/SS | Inflation Pressure | Recommened load,kg (lbs) |
|------------------|-----|-------------------------|------|-----|------|----|-------|--------------------|--------------------------|
| | | SW | OD | | | | | | Speed,km/h(mph) |
| | | mm | mm | | | | | | Constant Load |
| | | in | in | | | | | | |
| 405/70-20 IND | 13 | 405 | 1080 | 505 | 3210 | | 165 B | 5.8 | 5150 |
| | | 15.9 | 42.5 | 20 | 126 | | | 83 | 11340 |