

FARMAX R70/R75

- Landwirtschaft
- Traktor
- Radial

(Größerer Winkel und Überlappung der Laschen in der Mitte) Bessere Straßentauglichkeit

(Profiltiefe R1-W) Längere Reifenlebensdauer



(Abgerundete Schulter) Reduzierte Schäden an Boden und Ernte

(Niedrigerer Winkel an der Schulter) Überragende Traktion

Size	Rim
200/70R16	W6
240/70R16	W8
260/70R16	W8
260/70R20	W8
280/70R16	W8L
280/70R18	W8L
280/70R20	W8
300/70R20	W9
300/70R20	W9
320/70R20	W10

320/70R20	W10
320/70R24	W10
320/70R28	W10
360/70R20	W11
360/70R20	W11
360/70R24	W11
360/70R28	W11
380/70R20	W12
380/70R20	W12
380/70R24	W12
380/70R28	W12
400/75R38	W13
420/70R24	W13
420/70R28	W13
420/70R30	W13
480/70R24	W15L
480/70R28	W15L
480/70R28	W15L
480/70R30	W15L
480/70R30	W15L
480/70R34	W15L
480/70R34	W15L
480/70R34	W15L
480/70R38	W15L
520/70R30	W16L
520/70R34	W16L
520/70R34	W16L
520/70R38	W16L
580/70R38	W18L
580/70R38	W18L
580/70R38	W18L
600/70R28	DW20B
600/70R30	DW20B
600/70R30	DW20B
620/70R42	DW20B
620/70R42	DW20B
710/70R38	DW23B
710/70R38	DW23B

710/70R42	DW23B
580/70R42	W18L

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
200/70 R16	W6	197 7.8	686 27.0	316 12.4	2069 81.5	94D/9 7A8	0.8	810	530	430	400	380	370	350	
							12	1780	1170	950	880	840	810	770	
							1.2	1040	680	550	520	490	470	450	
							17	2290	1500	1210	1150	1080	1040	990	
							1.8	1310	860	700	660	620	600	570	
							26	2890	1890	1540	1450	1370	1320	1260	
							2.4	1540	1010	820	770	730	700	670	
							35	3390	2220	1810	1700	1610	1540	1480	

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	bar	Static
in	in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40
240/70 R16	W8 W9	244 9.6	742 29.2	338 13.3	2215 87.2	104D/ 107A8	0.8	1080	710	580	540	510	490	470	
							12	2380	1560	1280	1190	1120	1080	1040	
							1.2	1380	900	740	690	660	630	600	
							17	3040	1980	1630	1520	1450	1390	1320	
							1.8	1750	1140	930	870	830	800	760	
							26	3850	2510	2050	1920	1830	1760	1670	
							2.4	2070	1350	1110	1040	990	950	900	
							35	4560	2970	2440	2290	2180	2090	1980	

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	bar	Static
in	in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40
260/70 R16	W8 W9	258 10.2	770 30.3	349 13.7	2298 90.5	109D/ 112A8	0.8	1240	810	660	620	590	570	540	
							12	2730	1780	1450	1370	1300	1260	1190	
							1.2	1590	1040	850	790	760	720	690	
							17	3500	2290	1870	1740	1670	1590	1520	
							1.8	2000	1310	1070	1000	950	910	870	
							26	4410	2890	2360	2200	2090	2000	1920	
							2.4	2370	1550	1270	1180	1130	1080	1030	
							35	5220	3410	2800	2600	2490	2380	2270	

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	bar	Static
in	in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40
260/70 R20	W8 W9	260 10.2	872 34.3	400 15.7	2602 102.4	113D/ 116A8	0.8	1400	920	750	700	670	640	610	
							12	3080	2030	1650	1540	1480	1410	1340	
							1.4	1930	1260	1030	970	920	880	840	
							20	4250	2780	2270	2140	2030	1940	1850	
							2.0	2370	1550	1270	1180	1130	1080	1030	
							29	5220	3410	2800	2600	2490	2380	2270	
							2.4	2650	1730	1410	1320	1260	1210	1150	
							35	5840	3810	3110	2910	2780	2670	2530	

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
280/70 R16	W8L W9 W10	282 11.1	798 31.4	360 14.2	2382 93.8	112D/ 115A8		0.8	1360	890	730	680	650	620	590
								12	3000	1960	1610	1500	1430	1370	1300
								1.4	1890	1230	1010	940	900	860	820
								20	4160	2710	2220	2070	1980	1890	1810
								2.0	2320	1520	1240	1160	1110	1060	1010
								29	5110	3350	2730	2560	2440	2330	2220
								2.4	2580	1680	1380	1290	1230	1180	1120
35	5680	3700	3040	2840	2710	2600	2470								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
280/70 R18	W8L W9 W10	282 11.1	849 33.4	386 15.2	2534 99.8	114D/ 117A8		0.8	1430	930	760	710	680	650	620
								12	3150	2050	1670	1560	1500	1430	1370
								1.4	1980	1290	1060	990	940	900	860
								20	4360	2840	2330	2180	2070	1980	1890
								2.0	2440	1590	1300	1220	1160	1110	1060
								29	5370	3500	2860	2690	2560	2440	2330
								2.4	2710	1770	1450	1360	1290	1240	1180
35	5970	3900	3190	3000	2840	2730	2600								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
280/70 R20	W8 W9 W10	290 11.4	900 35.4	411 16.2	2686 105.7	116D/ 119A8		0.8	1920	1250	1020	950	910	870	830
								12	4230	2750	2250	2090	2000	1920	1830
								1.0	2190	1430	1170	1090	1040	1000	950
								15	4820	3150	2580	2400	2290	2200	2090
								1.4	2670	1740	1430	1330	1270	1220	1160
								20	5880	3830	3150	2930	2800	2690	2560
								1.6	2880	1880	1540	1440	1370	1310	1250
23	6340	4140	3390	3170	3020	2890	2750								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
300/70 R20	W9 W10	295 11.6	952 37.5	434 17.1	2826 111.3	120D/ 123A8		0.8	1680	1100	900	840	800	770	730
								12	3700	2420	1980	1850	1760	1700	1610
								1.8	2710	1770	1450	1360	1290	1240	1180
								26	5970	3900	3190	3000	2840	2730	2600
								2.1	2970	1940	1590	1480	1410	1350	1290
								30	6540	4270	3500	3260	3110	2970	2840
								2.4	3220	2100	1720	1610	1530	1470	1400
35	7090	4630	3790	3550	3370	3240	3080								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
300/70 R20	W9 W10	295 11.6	952 37.5	434 17.1	2826 111.3	110D/ 113A8		0.8	1680	1100	900	840	800	770	730
								12	3700	2420	1980	1850	1760	1700	1610
								1.2	2070	1350	1110	1040	990	950	900
								1.7	4560	2970	2440	2290	2180	2090	1980
								1.4	2250	1470	1210	1130	1070	1030	980
								20	4960	3240	2670	2490	2360	2270	2160
								1.6	2440	1590	1300	1220	1160	1110	1060
								23	5370	3500	2860	2690	2560	2440	2330

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
320/70 R20	W10 W9 W11	320 12.6	982 38.7	444 17.5	2909 114.5	113D/ 116A8		0.8	1770	1160	950	890	840	810	770
								12	3900	2560	2090	1960	1850	1780	1700
								1.2	2230	1460	1190	1120	1060	1020	970
								1.7	4910	3220	2620	2470	2330	2250	2140
								1.4	2440	1590	1300	1220	1160	1110	1060
								20	5370	3500	2860	2690	2560	2440	2330
								1.6	2650	1730	1410	1320	1260	1210	1150
								23	5840	3810	3110	2910	2780	2670	2530

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
320/70 R20	W10 W9 W11	320 12.6	982 38.7	444 17.5	2909 114.5	123D/ 126A8		0.8	1770	1160	950	890	840	810	770
								12	3900	2560	2090	1960	1850	1780	1700
								1.8	3010	1970	1610	1510	1430	1380	1310
								2.6	6630	4340	3550	3330	3150	3040	2890
								2.1	3290	2150	1760	1640	1570	1500	1430
								30	7250	4740	3880	3610	3460	3300	3150
								2.4	3570	2330	1910	1780	1700	1630	1550
								35	7860	5130	4210	3920	3740	3590	3410

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
320/70 R24	W10 W9 W11	320 12.6	1095 43.1	499 19.6	3261 128.4	116D/ 119A8		0.8	1930	1260	1030	970	920	880	840
								12	4250	2780	2270	2140	2030	1940	1850
								1.2	2440	1590	1300	1220	1160	1110	1060
								1.7	5370	3500	2860	2690	2560	2440	2330
								1.4	2670	1740	1430	1330	1270	1220	1160
								20	5880	3830	3150	2930	2800	2690	2560
								1.6	2880	1880	1540	1440	1370	1310	1250
								23	6340	4140	3390	3170	3020	2890	2750

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
320/70 R28	W10 W9 W11	320 12.6	1190 46.9	548 21.6	3563 140.3	119D/ 122A8		0.8	2090	1370	1120	1050	1000	960	910
								12	4600	3020	2470	2310	2200	2110	2000
								1.2	2650	1730	1410	1320	1260	1210	1150
								17	5840	3810	3110	2910	2780	2670	2530
								1.4	2900	1890	1550	1450	1380	1320	1260
								20	6390	4160	3410	3190	3040	2910	2780
								1.6	3130	2040	1670	1560	1490	1430	1360
								23	6890	4490	3680	3440	3280	3150	3000

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
360/70 R20	W11 W12 W10	360 14.2	1042 41.0	468 18.4	3074 121.0	120D/ 123A8		0.8	2140	1400	1140	1070	1020	980	930
								12	4710	3080	2510	2360	2250	2160	2050
								1.0	2440	1590	1300	1220	1160	1110	1060
								15	5370	3500	2860	2690	2560	2440	2330
								1.2	2710	1770	1450	1360	1290	1240	1180
								17	5970	3900	3190	3000	2840	2730	2600
								1.6	3220	2100	1720	1610	1530	1470	1400
								23	7090	4630	3790	3550	3370	3240	3080

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
360/70 R20	W11 W12 W10	360 14.2	1042 41.0	468 18.4	3074 121.0	129D/ 132A8		0.8	2140	1400	1140	1070	1020	980	930
								12	4710	3080	2510	2360	2250	2160	2050
								1.4	3110	2030	1660	1550	1480	1420	1350
								20	6850	4470	3660	3410	3260	3130	2970
								2.0	3820	2490	2040	1910	1820	1740	1660
								29	8410	5480	4490	4210	4010	3830	3660
								2.4	4260	2780	2280	2130	2030	1940	1850
								35	9380	6120	5020	4690	4470	4270	4070

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
360/70 R24	W11 W12 W10	360 14.2	1152 45.4	522 20.6	3420 134.6	122D/ 125A8		0.8	2300	1500	1230	1150	1100	1050	1000
								12	5070	3300	2710	2530	2420	2310	2200
								1.0	2620	1710	1400	1310	1250	1200	1140
								15	5770	3770	3080	2890	2750	2640	2510
								1.4	3200	2090	1710	1600	1520	1460	1390
								20	7050	4600	3770	3520	3350	3220	3060
								1.6	3450	2250	1850	1730	1640	1580	1500
								23	7600	4960	4070	3810	3610	3480	3300

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
360/70 R28	W11 W12 W10	360 14.2	1251 49.3	572 22.5	3734 147.0	125D/ 128A8		0.8	2530	1650	1350	1270	1200	1160	1100
								12	5570	3630	2970	2800	2640	2560	2420
								1.2	3220	2100	1720	1610	1530	1470	1400
								1.7	7090	4630	3790	3550	3370	3240	3080
								1.4	3520	2300	1880	1760	1680	1610	1530
								20	7750	5070	4140	3880	3700	3550	3370
								1.6	3800	2480	2030	1900	1810	1730	1650
								23	8370	5460	4470	4190	3990	3810	3630

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
380/70 R20	W12 W13 W11	380 15.0	1082 42.6	486 19.1	3185 125.4	132D/ 135A8		0.8	2300	1500	1230	1150	1100	1050	1000
								12	5070	3300	2710	2530	2420	2310	2200
								1.2	2920	1910	1560	1460	1390	1330	1270
								1.7	6430	4210	3440	3220	3060	2930	2800
								1.4	3200	2090	1710	1600	1520	1460	1390
								20	7050	4600	3770	3520	3350	3220	3060
								1.6	3450	2250	1850	1730	1640	1580	1500
								23	7600	4960	4070	3810	3610	3480	3300

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
380/70 R20	W12 W13 W11	380 15.0	1082 42.6	486 19.1	3185 125.4	122D/ 125A8		0.8	2300	1500	1230	1150	1100	1050	1000
								12	5070	3300	2710	2530	2420	2310	2200
								1.6	3450	2250	1850	1730	1640	1580	1500
								23	7600	4960	4070	3810	3610	3480	3300
								1.8	3890	2540	2080	1940	1850	1770	1690
								26	8570	5590	4580	4270	4070	3900	3720
								2.4	4600	3000	2460	2300	2190	2100	2000
								35	10130	6610	5420	5070	4820	4630	4410

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	bar	Static
in	in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40
380/70 R24	W12 W11 W13	380 15.0	1190 46.9	540 21.3	3514 138.3	125D/ 128A8		0.8	2530	1650	1350	1270	1200	1160	1100
								12	5570	3630	2970	2800	2640	2560	2420
								1.0	2880	1880	1540	1440	1370	1310	1250
								1.5	6340	4140	3390	3170	3020	2890	2750
								1.3	3360	2190	1800	1680	1600	1530	1460
								19	7400	4820	3960	3700	3520	3370	3220
								1.6	3800	2480	2030	1900	1810	1730	1650
								23	8370	5460	4470	4190	3990	3810	3630

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
380/70 R28	W12 W13 W11	380 15.0	1293 50.9	589 23.2	3843 151.3	127D/ 130A8		0.8	2690	1760	1440	1350	1280	1230	1170
								12	5930	3880	3170	2970	2820	2710	2580
								1.2	3400	2220	1820	1700	1620	1550	1480
								17	7490	4890	4010	3740	3570	3410	3260
								1.4	3730	2430	1990	1860	1770	1700	1620
								20	8220	5350	4380	4100	3900	3740	3570
								2.4	4600	3000	2460	2300	2190	2100	2000
								35	10130	6610	5420	5070	4820	4630	4410

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
400/75 R38	W13 W12 W14	404 15.9	1565 61.6	723 28.5	4646 182.9	138D/ 141A8		0.8	3610	2360	1930	1810	1720	1650	1570
								12	7950	5200	4250	3990	3790	3630	3460
								1.0	4120	2690	2200	2060	1960	1880	1790
								15	9070	5930	4850	4540	4320	4140	3940
								1.4	5010	3270	2680	2510	2390	2290	2180
								20	11040	7200	5900	5530	5260	5040	4800
								1.6	5430	3540	2900	2710	2580	2480	2360
								23	11960	7800	6390	5970	5680	5460	5200

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
420/70 R24	W13 W12 W14	430 16.9	1248 49.1	563 22.2	3683 145.0	130D/ 133A8		0.8	2900	1890	1550	1450	1380	1320	1260
								12	6390	4160	3410	3190	3040	2910	2780
								1.0	3310	2160	1770	1660	1580	1510	1440
								15	7290	4760	3900	3660	3480	3330	3170
								1.3	3860	2520	2070	1930	1840	1760	1680
								19	8500	5550	4560	4250	4050	3880	3700
								1.6	4370	2850	2340	2190	2080	2000	1900
								23	9630	6280	5150	4820	4580	4410	4190

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	mm	bar	Static
in	in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40
420/70 R28	W13 W12 W14	430 16.9	1349 53.1	614 24.2	3985 156.9	133D/ 136A8		0.8	3150	2060	1690	1580	1500	1440	1370
								12	6940	4540	3720	3480	3300	3170	3020
								1.0	3590	2340	1920	1790	1710	1640	1560
								15	7910	5150	4230	3940	3770	3610	3440
								1.3	4190	2730	2240	2090	1990	1910	1820
								19	9230	6010	4930	4600	4380	4210	4010
								1.6	4740	3090	2530	2370	2260	2160	2060
								23	10440	6810	5570	5220	4980	4760	4540

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
420/70 R30	W13 W12 W14	430 16.9	1398 55.0	636 25.0	4155 163.6	134D/ 137A8		0.8	3240	2120	1730	1620	1540	1480	1410
								12	7140	4670	3810	3570	3390	3260	3110
								1.0	3700	2420	1980	1850	1760	1690	1610
								15	8150	5330	4360	4070	3880	3720	3550
								1.4	4510	2940	2410	2250	2150	2060	1960
								20	9930	6480	5310	4960	4740	4540	4320
								1.6	4880	3180	2610	2440	2320	2230	2120
								23	10750	7000	5750	5370	5110	4910	4670

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R24	W15L W14L W16L	490 19.3	1316 51.8	588 23.1	3870 152.4	138D/ 141A8		0.8	3610	2360	1930	1810	1720	1650	1570
								12	7950	5200	4250	3990	3790	3630	3460
								1.0	4120	2690	2200	2060	1960	1880	1790
								15	9070	5930	4850	4540	4320	4140	3940
								1.4	5010	3270	2680	2510	2390	2290	2180
								20	11040	7200	5900	5530	5260	5040	4800
								1.6	5430	3540	2900	2710	2580	2480	2360
								23	11960	7800	6390	5970	5680	5460	5200

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R28	W15L W14L W16L	490 19.3	1421 55.9	640 25.2	4183 164.7	140D/ 143A8		0.8	3840	2510	2050	1920	1830	1750	1670
								12	8460	5530	4520	4230	4030	3850	3680
								1.0	4370	2850	2340	2190	2080	2000	1900
								15	9630	6280	5150	4820	4580	4410	4190
								1.4	5310	3470	2840	2660	2530	2430	2310
								20	11700	7640	6260	5860	5570	5350	5090
								1.6	5750	3750	3080	2880	2740	2630	2500
								23	12670	8260	6780	6340	6040	5790	5510

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R28	W15L W14L W16L	490 19.3	1421 55.9	640 25.2	4183 164.7	151D/ 154A8		0.8	3840	2510	2050	1920	1830	1750	1670
								12	8460	5530	4520	4230	4030	3850	3680
								1.8	5680	3710	3040	2840	2700	2590	2470
								26	12510	8170	6700	6260	5950	5700	5440
								2.5	6880	4490	3680	3440	3270	3140	2990
								36	15150	9890	8110	7580	7200	6920	6590
								3.2	7940	5180	4240	3970	3780	3620	3450
								46	17490	11410	9340	8740	8330	7970	7600

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R30	W15L W14L W16L	490 19.3	1478 58.2	671 26.4	4377 172.3	141D/ 144A8		0.8	3960	2580	2120	1980	1880	1810	1720
								12	8720	5680	4670	4360	4140	3990	3790
								1.0	4510	2940	2410	2250	2150	2060	1960
								15	9930	6480	5310	4960	4740	4540	4320
								1.3	5240	3420	2800	2620	2500	2390	2280
								19	11540	7530	6170	5770	5510	5260	5020
								1.6	5920	3860	3170	2960	2820	2700	2575
								23	13040	8500	6980	6520	6210	5950	5670

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R30	W15L W14L W16L	490 19.3	1478 58.2	671 26.4	4377 172.3	147D/ 150A8		0.8	3730	2430	1990	1860	1770	1700	1620
								12	8220	5350	4380	4100	3900	3740	3570
								1.2	4720	3080	2520	2360	2240	2150	2050
								17	10400	6780	5550	5200	4930	4740	4520
								1.4	5380	3510	2880	2690	2560	2460	2340
								20	11850	7730	6340	5930	5640	5420	5150
								2.0	6350	4530	3390	3170	3020	2900	2760
								29	13990	9980	7470	6980	6650	6390	6080
								2.4	7070	4610	3780	3540	3370	3230	3075
								35	15570	10150	8330	7800	7420	7110	6770

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R34	W15L W14L W16L	490 19.3	1580 62.2	722 28.4	4696 184.9	143D/ 146A8		0.8	4160	2720	2230	2080	1980	1900	1810
								12	9160	5990	4910	4580	4360	4190	3990
								1.2	5290	3450	2830	2650	2520	2420	2300
								17	11650	7600	6230	5840	5550	5330	5070
								1.4	5800	3780	3100	2900	2760	2650	2520
								20	12780	8330	6830	6390	6080	5840	5550
								1.6	6270	4090	3350	3130	2980	2860	2725
								23	13810	9010	7380	6890	6560	6300	6000

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Tractor Application							
		mm	mm					mm	mm	mm	mm	mm	bar	Static	10
in	in	in	in	in	in	in	psi	Static	6	12	19	25	31	40	
480/70 R34	W15L W14L W16L	490 19.3	1580 62.2	722 28.4	4696 184.9	149D/ 152A8		0.8	4160	2720	2230	2080	1980	1900	1810
								12	9160	5990	4910	4580	4360	4190	3990
								1.8	6330	4130	3380	3160	3010	2890	2750
								26	13940	9100	7440	6960	6630	6370	6060
								2.0	6720	4380	3590	3360	3200	3070	2920
								29	14800	9650	7910	7400	7050	6760	6430

								2.4	7480	4880	4000	3740	3560	3410	3250
								35	16480	10750	8810	8240	7840	7510	7160

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					mm	mm	mm	bar	Static	10	20	30
480/70 R34	W15L W14L W16L	490 19.3	1580 62.2	722 28.4	4696 184.9	155D/ 158A8		0.8	4160	2720	2230	2080	1980	1900	1810
								12	9160	5990	4910	4580	4360	4190	3990
								2.6	8050	5250	4310	4030	3830	3680	3500
								38	17730	11560	9490	8880	8440	8110	7710
								2.8	8400	5480	4490	4200	4000	3830	3650
								41	18500	12070	9890	9250	8810	8440	8040
								3.1	8910	5810	4770	4460	4240	4070	3875
								45	19630	12800	10510	9820	9340	8960	8540

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					mm	mm	mm	bar	Static	10	20	30
480/70 R38	W15L W14L W16L	500 19.7	1680 66.1	773 30.4	5040 198.4	145D/ 148A8		0.8	4440	2900	2370	2220	2110	2030	1930
								12	9780	6390	5220	4890	4650	4470	4250
								1.0	5060	3300	2710	2530	2410	2310	2200
								15	11150	7270	5970	5570	5310	5090	4850
								1.4	6160	4020	3300	3080	2930	2810	2680
								20	13570	8850	7270	6780	6450	6190	5900
								1.6	6670	4350	3570	3340	3180	3050	2900
								23	14690	9580	7860	7360	7000	6720	6390

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					mm	mm	mm	bar	Static	10	20	30
520/70 R30	W16L W15L W18L	530 20.9	1536 60.5	694 27.3	4537 178.6	145D/ 148A8		0.8	4440	2900	2370	2220	2110	2030	1930
								12	9780	6390	5220	4890	4650	4470	4250
								1.0	5060	3300	2710	2530	2410	2310	2200
								15	11150	7270	5970	5570	5310	5090	4850
								1.3	5910	3860	3160	2960	2810	2700	2570
								19	13020	8500	6960	6520	6190	5950	5660
								1.6	6670	4350	3570	3340	3180	3050	2900
								23	14690	9580	7860	7360	7000	6720	6390

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					mm	mm	mm	bar	Static	10	20	30
520/70 R34	W16L W15L W18L	516 20.3	1640 64.6	743 29.3	4920 193.7	148D/ 151A8		0.8	4830	3150	2580	2420	2300	2210	2100
								12	10640	6940	5680	5330	5070	4870	4630
								1.0	5500	3590	2940	2750	2620	2510	2390
								15	12110	7910	6480	6060	5770	5530	5260
								1.4	6690	4370	3580	3350	3190	3060	2910

								20	14740	9630	7890	7380	7030	6740	6410
								1.6	7250	4730	3870	3620	3450	3310	3150
								23	15970	10420	8520	7970	7600	7290	6940

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					Static	10	20	30	40	50	65	
							bar	Static	6	12	19	25	31	40	
							psi	Static	6	12	19	25	31	40	
520/70 R34	W16L W15L W18L	516 20.3	1640 64.6	743 29.3	4920 193.7	168D/ 171A8	0.8	4830	3150	2580	2420	2300	2210	2100	
							12	10640	6940	5680	5330	5070	4870	4630	
							1.8	7750	5060	4150	3880	3690	3540	3370	
							26	17070	11150	9140	8550	8130	7800	7420	
							2.8	10030	6540	5360	5010	4770	4580	4360	
							41	22090	14410	11810	11040	10510	10090	9600	
							4.3	12880	8400	6890	6440	6130	5880	5600	
62	28370	18500	15180	14190	13500	12950	12330								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					Static	10	20	30	40	50	65	
							bar	Static	6	12	19	25	31	40	
							psi	Static	6	12	19	25	31	40	
520/70 R38	W16L W15L W18L	530 20.9	1749 68.9	800 31.5	5204 204.9	150D/ 153A8	0.8	4876	3180	2512	2438	2321	2226	2120	
							12	10740	7000	5530	5370	5110	4900	4670	
							1.0	6268	4088	3229	3134	2984	2861	2725	
							15	13810	9000	7110	6900	6570	6300	6000	
							1.3	6900	4500	3555	3450	3285	3150	3000	
							19	15200	9910	7830	7600	7240	6940	6610	
							1.6	7705	5025	3970	3853	3668	3518	3350	
23	16970	11070	8740	8490	8080	7750	7380								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					Static	10	20	30	40	50	65	
							bar	Static	6	12	19	25	31	40	
							psi	Static	6	12	19	25	31	40	
580/70 R38	W18L	577 22.7	1827 71.9	832 32.8	5420 213.4	180D/ 183A8	0.8	5930	3870	3170	2970	2830	2710	2580	
							12	13060	8520	6980	6540	6230	5970	5680	
							4.0	13800	9000	7380	6900	6570	6300	6000	
							58	30400	19820	16260	15200	14470	13880	13220	
							5.0	17600	11480	9410	8800	8380	8030	7650	
							73	38770	25290	20730	19380	18460	17690	16850	
							5.4	18400	12000	9840	9200	8760	8400	8000	
78	40530	26430	21670	20260	19300	18500	17620								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
		mm	mm					Tractor Application							
		in	in					Static	10	20	30	40	50	65	
							bar	Static	6	12	19	25	31	40	
							psi	Static	6	12	19	25	31	40	
580/70 R38	W18L	577 22.7	1827 71.9	832 32.8	5420 213.4	155D/ 158A8	0.8	5930	3870	3170	2970	2830	2710	2580	
							12	13060	8520	6980	6540	6230	5970	5680	
							1.0	6760	4410	3620	3380	3220	3090	2940	
							15	14890	9710	7970	7440	7090	6810	6480	

							1.2	7520	4910	4020	3760	3580	3430	3270
							17	16560	10810	8850	8280	7890	7560	7200
							1.4	8230	5370	4400	4120	3920	3760	3580
							20	18130	11830	9690	9070	8630	8280	7890
							1.6	8910	5810	4770	4460	4240	4070	3875
							23	19630	12800	10510	9820	9340	8960	8540

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)						
		SW	OD					Speed,km/h(mph)						
		mm	mm					Tractor Application						
		in	in					Static	10	20	30	40	50	65
		bar	10	20	30	40	50	65						
		psi	6	12	19	25	31	40						
580/70 R38	W18L	577 22.7	1827 71.9	832 32.8	5420 213.4	170D/ 173A8	0.8	5930	3870	3170	2970	2830	2710	2580
							12	13060	8520	6980	6540	6230	5970	5680
							2.4	10240	6680	5470	5120	4870	4670	4450
							35	22560	14710	12050	11280	10730	10290	9800
							2.8	11200	7310	5990	5600	5330	5110	4870
							41	24670	16100	13190	12330	11740	11260	10730
							3.4	12560	8190	6720	6280	5980	5730	5460
							49	27670	18040	14800	13830	13170	12620	12030
							4.0	13800	9000	7380	6900	6570	6300	6000
58	30400	19820	16260	15200	14470	13880	13220							

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)						
		SW	OD					Speed,km/h(mph)						
		mm	mm					Tractor Application						
		in	in					Static	10	20	30	40	50	65
		bar	10	20	30	40	50	65						
		psi	6	12	19	25	31	40						
600/70 R28	DW20 B DW18 L	611 24.1	1560 61.4	700 27.6	4582 180.4	161D/ 164A8	1.8	8210	5360	4390	4110	3910	3750	3570
							26	18080	11810	9670	9050	8610	8260	7860
							2.0	8740	5700	4670	4370	4160	3990	3800
							29	19250	12560	10290	9630	9160	8790	8370
							2.4	9730	6350	5200	4860	4630	4440	4230
							35	21430	13990	11450	10700	10200	9780	9320
							2.8	10640	6940	5690	5320	5060	4860	4625
							41	23440	15290	12530	11720	11150	10700	10190

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)						
		SW	OD					Speed,km/h(mph)						
		mm	mm					Tractor Application						
		in	in					Static	10	20	30	40	50	65
		bar	10	20	30	40	50	65						
		psi	6	12	19	25	31	40						
600/70 R30	DW20 B DW18 L	611 24.1	1621 63.8	725 28.5	4780 188.2	152D/ 155A8	0.8	5430	3540	2900	2710	2580	2480	2360
							12	11960	7800	6390	5970	5680	5460	5200
							1.0	6190	4040	3310	3090	2950	2820	2690
							15	13630	8900	7290	6810	6500	6210	5930
							1.3	7220	4710	3860	3610	3440	3300	3140
							19	15900	10370	8500	7950	7580	7270	6920
							1.6	8170	5330	4370	4080	3890	3730	3550
							23	18000	11740	9630	8990	8570	8220	7820

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)						
		SW	OD					Speed,km/h(mph)						
		mm	mm					Tractor Application						
		mm	mm					Static	10	20	30	40	50	65

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
								Tractor Application							
								bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
600/70 R30	DW20 B DW18 L	611 24.1	1621 63.8	725 28.5	4780 188.2	158D/ 161A8	0.8	5430	3540	2900	2710	2580	2480	2360	
							12	11960	7800	6390	5970	5680	5460	5200	
							1.2	6900	4500	3690	3450	3290	3150	3000	
							17	15200	9910	8130	7600	7250	6940	6610	
							1.6	8170	5330	4370	4080	3890	3730	3550	
							23	18000	11740	9630	8990	8570	8220	7820	
							2.4	12080	7880	6460	6040	5750	5510	5250	
35	26610	17360	14230	13300	12670	12140	11560								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
								Tractor Application							
								bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
620/70 R42	DW20 B W18L	625 24.6	1935 76.2	881 34.7	5745 226.2	166D/ 169A8	0.8	6390	4170	3420	3200	3040	2920	2780	
							12	14070	9190	7530	7050	6700	6430	6120	
							1.4	8880	5790	4750	4440	4230	4050	3860	
							20	19560	12750	10460	9780	9320	8920	8500	
							2.0	10950	7140	5850	5470	5210	5000	4760	
							29	24120	15730	12890	12050	11480	11010	10480	
							2.4	12190	7950	6520	6100	5800	5570	5300	
35	26850	17510	14360	13440	12780	12270	11670								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
								Tractor Application							
								bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
620/70 R42	DW20 B W18L	625 24.6	1935 76.2	881 34.7	5745 226.2	173D/ 176A8	0.8	6390	4170	3420	3200	3040	2920	2780	
							12	14070	9190	7530	7050	6700	6430	6120	
							1.6	9610	6270	5140	4810	4580	4390	4180	
							23	21170	13810	11320	10590	10090	9670	9210	
							1.8	10300	6720	5510	5150	4910	4700	4480	
							26	22690	14800	12140	11340	10810	10350	9870	
							3.4	14950	9750	8000	7480	7120	6830	6500	
49	32930	21480	17620	16480	15680	15040	14320								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		SW	OD					Speed,km/h(mph)							
								Tractor Application							
								bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
710/70 R38	DW23 B DW25 B	715 28.1	1959 77.1	881 34.7	5785 227.8	172D/ 175A8	0.8	7610	4970	4070	3810	3620	3480	3310	
							12	16760	10950	8960	8390	7970	7670	7290	
							1.6	11430	7460	6110	5720	5440	5220	4970	
							23	25180	16430	13460	12600	11980	11500	10950	
							2.0	13020	8490	6960	6510	6200	5940	5660	
							29	28680	18700	15330	14340	13660	13080	12470	
							2.4	14490	9450	7750	7250	6900	6620	6300	
35	31920	20810	17070	15970	15200	14580	13880								

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)						
		SW	OD					Speed,km/h(mph)						
								Tractor Application						

		mm	mm	mm	mm	mm	bar	Static	10	20	30	40	50	65
		in	in	in	in	in	psi	Static	6	12	19	25	31	40
710/70 R38	DW23 B DW25 B	715 28.1	1959 77.1	881 34.7	5785 227.8	178D/ 181A8	0.8	7610	4970	4070	3810	3620	3480	3310
							12	16760	10950	8960	8390	7970	7670	7290
							1.4	10650	6950	5690	5320	5070	4860	4630
							20	23460	15310	12530	11720	11170	10700	10200
							1.8	12330	8040	6590	6160	5870	5630	5360
							26	27160	17710	14520	13570	12930	12400	11810
							3.2	17250	11250	9230	8630	8210	7880	7500
							46	38000	24780	20330	19010	18080	17360	16520

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)									
								Speed,km/h(mph)									
		SW	OD	mm	mm	mm	mm	mm	bar	Tractor Application							
		mm	mm							Static	10	20	30	40	50	65	
		in	in							psi	Static	6	12	19	25	31	40
710/70 R42	DW23 B DW25 B	715 28.1	2061 81.1	932 36.7	6119 240.9	173D/ 176A8	0.8	7870	5130	4210	3930	3740	3590	3420			
							12	17330	11300	9270	8660	8240	7910	7530			
							1.2	9980	6510	5340	4990	4750	4560	4340			
							17	21980	14340	11760	10990	10460	10040	9560			
							1.6	11800	7700	6310	5900	5620	5390	5130			
							23	25990	16960	13900	13000	12380	11870	11300			
							2.0	13430	8760	7180	6720	6390	6130	5840			
							29	29580	19300	15810	14800	14070	13500	12860			
							2.4	14950	9750	8000	7480	7120	6830	6500			
35	32930	21480	17620	16480	15680	15040	14320										

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)									
								Speed,km/h(mph)									
		SW	OD	mm	mm	mm	mm	mm	bar	Tractor Application							
		mm	mm							Static	10	20	30	40	50	65	
		in	in							psi	Static	6	12	19	25	31	40
580/70 R42	W18L	577 22.7	1827 71.9	838 33.0	5626 221.5	158D/ 161A8	0.8	6510	4250	3480	3250	3100	2970	2830			
							12	14340	9360	7670	7160	6830	6540	6230			
							1.0	4730	4850	3970	3710	3540	3390	3230			
							15	10420	10680	8740	8170	7800	7470	7110			
							1.4	9040	5900	4830	4520	4300	4130	3930			
							20	19910	13000	10640	9960	9470	9100	8660			
							1.6	9780	6380	5040	4890	4650	4460	4250			
							23	21540	14050	11100	10770	10240	9820	9360			