



Moving mountains together



EQUIPMENT - PARTS - SERVICE



FOTON

BJ4259(MT) TRACTOR (6x4)



ENGINE POWER

430 HP



BODY

18m³ tipper



Tank

700L



BIAGROUP.COM

BJ4259- MT

Basic Info	Function Drive Style Steering Wheel Position Platform Work Conditions Vehicle Model	<ul style="list-style-type: none"> • Tractor head • 6x4 • Lef hand • GTL • Standard type • BJ4259SMFKB-26
Complete Vehicle Dimension Parameters	Wheelbase(mm) Long(mm) Width(mm) Height(mm) Tread(front)(mm) Tread(rear)(mm)	<ul style="list-style-type: none"> • 3300+1350 • 6940 • 2500 • 3150 • 2005 • 1800
Complete Vehicle Dimension Parameters	Chassis Kerb Weight(kg) GCW(t)	<ul style="list-style-type: none"> • 10200 • 90
Complete Vehicle Mass Parameter	Maximum Speed (km/h) Maximum Climbing Capacity, %(full load)	<ul style="list-style-type: none"> • 89(4.2) • 20(4.2)
Cabin	Body Type Carrying Number	<ul style="list-style-type: none"> • Flat roof, all welded steel cab, 4-points spring suspension cab, manual hydraulic cab tilting, adjustable driver's seat(pneumatic), seatbelt for driver and co-driver, manual rear-view mirrors and windows, central locking, MP3 + Radio + USB • 2 seats + 1 bunk
Engine	Engine Model Engine Type Displacement (cc) Max Power (kw/ps/rpm) Max Torque (Nm/rpm) Engine Brand Emission	<ul style="list-style-type: none"> • ISGe3-400 • Inline six-cylinder, four-stroke, water cooled, turbocharged, intercooled, direct injection, common rail diesel engine • 11,800 • 294/400/1900 • 2000/1000-1400 • CUMMINS • Euro III
Clutch	Clutch Type Plate Diameter(mm) Operating System	<ul style="list-style-type: none"> • Single, dry type diaphragm sping • φ430 • Manual hydraulic pneumatic
Gearbox	Gearbox Model Gearbox Type Gearbox Brand Numbers of Gears PTO	<ul style="list-style-type: none"> • HW23712 • MT • FOTON AUMAN • 12 Forward and 2 Reverse -
Brake	Service Brake Parking Brake Auxiliary Brake	<ul style="list-style-type: none"> • Dual circuits pneumatic brake • Energy-accumulating spring air cut-off brake • Engine brake
Suspension	Front Suspension/Leaf Spring Number Rear Suspension/Leaf Spring Number	<ul style="list-style-type: none"> • Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar, 9 pieces • Longitudinal leaf spring with balance suspension, 12 pieces
Front Axle	Capacity(kg) Front Axle BrakeType	<ul style="list-style-type: none"> • 7500 • Drum brakes
Rear Axle	Type Capacity(kg) Gear Ratio Rear Axle Brake Type	<ul style="list-style-type: none"> • Double reduction(BENZ Technology) • 2 x 16000 • 4.2 • Drum brakes
Tyre	Tyre Size Numbers of Tyres	<ul style="list-style-type: none"> • Standard:13R22.5, Optional:12R22.5, 315/80R22.5, 295/80R22.5 • 10+1
Frame	External Width(mm) Stringer Cross Section(mm)	<ul style="list-style-type: none"> • 900/780 • 225/286×80×(8+5)
Steering	Type Steering Wheel	<ul style="list-style-type: none"> • Hydraulic steering with power assistance • Adjustable
Fuel Tank	Type Capacity	<ul style="list-style-type: none"> • Aluminum fuel tank with lockable cap • 700L
Electrical System	Rated Voltage Battery	<ul style="list-style-type: none"> • 24V • 2x12V-165Ah
Other Configuration	ABS A/C Cruise Fifth Wheel ADR	<ul style="list-style-type: none"> • None - • None • 90#(3.5") • Standard: None, Optional: Yes