

**Series 2, Built-in oven, 60 x 60 cm,
Stainless steel
HHF133BS0B**



The built-in oven with 3D hot air: achieve perfect baking and roasting results on up to three levels simultaneously.

- **Red LED display control:** easy-to-use thanks to the time functions.
- **Pop-out controls:** Make the front of the oven easy to clean and give it a sleek look.
- **EcoClean Direct:** less cleaning effort thanks to a special coating of the rear wall that automatically absorbs grime.

Technical Data

Built-in / Free-standing: Built-in
Integrated Cleaning system: EcoClean Direct programme
Required niche size for installation (HxWxD): 575-597 x 560-568 x 550 mm
Dimensions: 595x594x548 mm
Dimensions of the packed product (HxWxD): 680x655x680 mm
Control Panel Material: Stainless steel
Door Material: Glass
Net weight: 31.5 kg
Usable volume of cavity: 66 l
Cooking method: Hotair gentle, Hot Air, Hot air grilling, Full width variable grill
Length electrical supply cord: 110 cm
EAN code: 4242005048359
Number of cavities (2010/30/EC): 1
Energy efficiency rating: A
Energy consumption per cycle forced air convection (2010/30/EC): 79 kWh/cycle
Energy efficiency index (2010/30/EC): 95.2 %
Connection rating: 2400 W
Fuse protection: 13 A
Voltage: 220-240 V
Frequency: 60; 50 Hz
Plug type: GB plug
Included accessories: 1 x insert grid, 1 x combination grid, 1 x universal pan



**Series 2, Built-in oven, 60 x 60 cm,
Stainless steel
HHF133BS0B**

**The built-in oven with 3D hot air: achieve
perfect baking and roasting results on up
to three levels simultaneously.**

Design

- LED-Display Control (Red)

Features

- Control panel lock
- Electronic clock timer
- Interior halogen light

Cleaning

- EcoClean Direct : back panel

Programmes/functions

- Oven with 4 cooking functions: heating methods: 3D Hotair, Hotair grilling, Hotair gentle, full width variable grill
- 1 x universal pan, 1 x combination grid, 1 x insert grid
- Integral cooling fan
- 110 cm Cable length
- Total connected load electric: 2.4 KW
- Nominal voltage: 220 - 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 575 mm - 597 mm x 560 mm - 568 mm x 550 mm
- "For-details-on-installation-and-ventilation requirements – please refer to the installation manual prior to fitting."

