

D-MAX-SERIES

*X-Rider Black
Spec Sheet*



#DARKHORSEPOWER

X-RIDER BLACK

www.isuzu.co.za f t

ISUZU

With you, for the long run

D-MAX DOUBLE CAB		ISUZU D-MAX 250 HO X-RIDER BLACK DOUBLE CAB	
DRIVE CONFIGURATION		4X2	
ENGINE		MASS / CAPACITIES	
Displacement (cc)	2 499	Towing Capacity (kg): Unbraked Trailer ⁽²⁾	750
No. of Cylinders	4	Towing Capacity / Rating (kg): Braked Trailer ⁽²⁾	2 100
Compression Ratio	18.1:1	Fuel Tank Capacity (Litres)	80
Bore X Stroke (mm)	95.4 X 87.4	LOADBOX FEATURES	
No. of Valves	16	Load Restraint Tiedown Brackets	4
Power @ r/min (kW)	100 @ 3 400	SAFETY FEATURES	
Torque @ r/min (Nm)	320 @ 1 800 – 2 800	Anti-Lock Braking System (ABS)	Standard
Turbocharger	Standard	Electronic Brake-Force Distribution (EBD)	Standard
Intercooler	Standard	Brake-Assist System (BAS)	Standard
FUEL CONSUMPTION⁽¹⁾		Electronic Stability Control (ESC) with Traction Control	Standard
Combined Cycle (l/100 km)	7.7	Hill-Start Assist (HSA)	Standard
Combined CO ₂ Emissions (g/km)	203	Hill Descent Control (HDC)	Standard
Fuel Type	Diesel	Side-Impact Protection Bars	Standard
TRANSMISSION		Height-Adjustable 3-Point Seatbelts	Standard
Transmission Type	5-Speed Manual	Seatbelt Pre-Tensioners	Standard
Gear Ratio: 1st	4.008	Rear Seatbelts	Standard
Gear Ratio: 2nd	2.301	Driver & Passenger Airbags	Standard
Gear Ratio: 3rd	1.427	Collapsible Steering Column	Standard
Gear Ratio: 4th	1.000	ISOFIX Child Seat Attachment	Standard
Gear Ratio: 5th	0.744	Warning Triangle Kit	Standard
Gear Ratio: Reverse	3.651	SECURITY FEATURES	
REAR DIFFERENTIAL		Remote-Controlled Central Locking	Standard
Differential Lock	Available	Remote Keyless Entry	Standard, Non-Integrated FOB
Axle Ratio: Final Drive	4.1	Anti-Theft Alarm System	Standard, Door-Activated
CHASSIS DESIGN		Transponder Immobiliser System	Standard
Front Wheel Suspension	Coil Over Shock	INTERIOR / EXTERIOR LIGHTING	
Rear Wheel Suspension	Leaf-Spring Overslung	Interior Courtesy Lamps	Standard
Shock Absorbers	Standard	Illuminated Entry	Standard
Suspension	High-Ride	Front Fog Lamps	Standard
Skid Plate Guard	Standard	Headlamps 'ON' Warning Buzzer	Standard
Engine Sump Guard	Standard	Rear Taillamps – Combination	Bulb
WHEELS / TYRES		High-Mounted Centre Stoplamp	Standard
Tyre Size	255 / 60 R18	EXTERIOR FEATURES	
Wheel (Size / Type)	18" X 7.5J Alloy	Front Bumper – Colour	Black
Spare Wheel (Size / Type)	18" X 7.5J Alloy	Rear Bumper – Colour	Black
Turning Circle: Curb-to-Curb (m)	12.8	Exterior Door Handles – Colour	Black
DIMENSIONS		Exterior Mirrors	Black – Power Adjustment
Length (mm)	5 294	Black Side-Steps	Standard
Width (mm)	1 860	Mudflaps	Front and Rear
Height (mm)	1 790	Wipers	Intermittent
Wheelbase (mm)	3 095	INTERIOR FEATURES	
Front / Rear Track (mm)	1 570 / 1 570	Power-Assisted Steering (PAS)	Hydraulic
Rear Overhang (mm)	1 301	Steering Column Adjustment	Tilt
Ground Clearance (mm)	225	Interior Door Handles – Colour	Black
Loadbox Length (mm)	1 485	Gearknob Trim	Urethane
Loadbox Width (mm)	1 535	Rear Seat Configuration	60:40-Split Bench Cushion
Loadbox Depth (mm)	470	Seat Adjustment	Driver – Manual Height, Reclining
Approach Angle (°)	30.0	Storage Pockets behind Front Seats	Standard
Departure Angle (°)	21.4	Floor Trim	Carpet with Heel Mat (x 1)
Breakover Angle (°)	22.4	Driver Footrest	Standard
Wading Depth (mm)	600	Air-Conditioner	Manual
MASS / CAPACITIES		Pollen Filter	Standard
Gross Axle Mass - Front (GA1) (kg)	1 350	Rear Heater Duct	Standard
Gross Axle Mass - Rear (GA2) (kg)	1 870	Inside Rear-View Mirror	Day / Night
Gross Vehicle Mass – (GVM) (kg)	3 000	INTERIOR FEATURES	
Gross Combined Mass – (GCM) (kg)	5 000	Sunvisor	Driver with Ticketholder and Passenger with Vanity Mirror
Tare Mass (kg)	1 930	Digital Clock	Standard
Payload (kg)	1 011	Dashboard Illumination Control	Standard
		Auxiliary 12-V Power Socket	1
		Lockable Glove Box	Standard
		Utility Box on Glove Box	Standard
		Door Trim with Storage Pockets and Integrated Cupholders	Standard
		Floor Tunnel / Console with Integrated Cupholder	Standard
		Centre Console Storage Box with Lid	Standard
		Fuelflap Remote	Standard
		Window Operation	Power – Front & Rear with Driver One-Touch, Jam Protection
		Rear Window	Fixed without Defogger
		INFOTAINMENT	
		Audio System	AM/FM Radio, Bluetooth® – Audio Streaming and Hands-Free Phone, 8" Touchscreen
		Audio Input Terminal: USB, Auxiliary, iPod	Standard
		Speakers	6
		Antenna	Standard
		OPTIONS	
		Differential lock	Available
		Sliding Rear Window	Available
		X-RIDER PACKAGE	
		X-RIDER Leather-Wrapped Steering Wheel with Audio Controls and Red Accent Stitching	Standard
		2 X Black Leather Bucket Seats with Red Accent Stitching and X-RIDER Logo on Headrest	Standard
		Gear Lever Cover with Red Accent Stitching	Standard
		Black Garnish Trim around Vents, Radio and Gear Shift	Standard
		Black Door Trim Inserts with Red 'X' Logo on Front Door Trim.	Standard
		18" All-Black Alloy Wheels	Standard
		Black Wheel Caps with Red Isuzu Logo	Standard
		Paint Colour	'Black Meet Kettle' Only
		X-RIDER Decal on Front Doors and Tailgate	Standard
		Black Roof Rails	Standard
		B-Pillar Blackout	Standard
		Black Front Bumper Guard	Standard
		Projector Headlamps with Integrated LED Daytime Running Lamps (DRL)	Standard
		Black Radiator Grille with Red Isuzu Badge	Standard
		Black X-RIDER Sportbar	Standard
		Tonneau Cover	Standard
		Towbar (2.1 T)	Standard
		WARRANTY / SERVICE INTERVALS	
		Warranty and Roadside Assistance	5 Years / 120 000 km
		Anti-Corrosion Warranty	5 Years / Unlimited km
		Service Plan	5 Years / 90 000 km
		Service Intervals	12 Months / 15 000 km

Notes:

(1) Fuel Economy and CO₂ data as per ECE R101 / SANS 20101 regulation. Note that the actual fuel consumption will depend on many factors including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.
(2) Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded. (e.g.: if a 3.0 L Diesel is towing 3,500 kg its maximum Vehicle mass is 2,500 kg in order to be within GCM).

The information herein is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Errors & Omissions Excepted. Model/s shown may differ. Date of print Aug 2019.