

[Home](#) ▶ [Equipment](#) ▶ [Loaders](#) ▶ [Skid-Steer Loaders](#) ▶ [S64](#)

# S64 Skid-Steer Loader



The Bobcat® S64 skid-steer loader brings new meaning to revolutionary performance.

- Industry-leading breakout force, rated operating capacities and faster cycle times
- One-piece, sealed and pressurized cab, clear visibility and operator-friendly controls
- Engineered to deliver maximum hydraulic performance
- Convenient access for routine maintenance
- Exceptional maneuverability

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)

[Download Brochure](#)



## S64 Overview

- The Bobcat® S64 skid-steer loader features improved cooling and enhanced machine protection.
- With a spacious, one-piece sealed and pressurized cab, ergonomic controls and optional clear side enclosure with automatic heating and air conditioning, it's clear why operators choose this powerful, agile machine.
- Featuring exceptional maneuverability and excellent turning and skidding abilities, the 68-hp S64 makes it easy to accomplish more when working in tight spaces.
- The Bobcat engine meets Tier 4 regulations without the need for a diesel particulate filter, which reduces downtime for regeneration and long-term maintenance costs.

## S64 Specifications

### S64 Key Specifications

Horsepower	68 hp
Rated Operating Capacity (ISO)	2,300 lb
Operating Weight	6974 lb
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min

Joystick Control

Optional

**Engine**

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	68 hp
Turbocharged Engine	yes

**Performance**

Rated Operating Capacity (ISO)	2,300 lb
Rated Operating Capacity 200 lb. Counterweight	2,450 lb
Tipping Load	4600 lb
Operating Weight	6974 lb
Travel Speed	7.4 mph
Travel Speed (2-speed option)	11 mph

**Capacities**

Fuel Tank	28.3 gal
-----------	----------

**Hydraulic System**

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min

**Dimension**

Length	135 in
Length without Attachment	107 in
Length with Standard Bucket	135 in
Width	64.6 in
Width (with bucket)	68 in
Height	80.5 in
Height with Operator Cab	80.5 in
Height to Bucket Hinge Pin	120 in

Reach @ Maximum Height	34.2 in
Turning Radius	80.1 in
Wheelbase	44.6 in

## Features

Joystick Control	Optional
Air Conditioning	Optional
Adjustable Seat	Standard
Backup Alarm	Standard
BICS System (Interlock)	Standard
Cab Enclosure	Optional
Sound Option	Optional
Cab Heater	Optional
Operating Lights	Standard
LED Front and Rear Lights	Standard
Standard Display (includes keyless start)	Standard
Speed Management	Included with SJC Option
Parking Brake	Wedge Brake
Radio	Optional
Rear Window	Standard
Top Window	Standard
Lift-Arm Support	Standard
Seat Belt	Standard
Suspension Seat	Standard
Heated Cloth Air-Ride Seat	Optional
Two Speed Travel	Optional
Deluxe Instrumentation	Not Applicable
Engine Shutdown	Standard
Hydraulic Bucket Positioning	Not Applicable
Dual-Direction Bucket Positioning	Optional
High Flow Option	Optional
Auxiliary Hydraulics	Standard

Spark Arrestor Muffler	DOC
Bob-Tach Attachment System	Standard
Power Bob-Tach	Optional
ACS (Switchable Controls)	Not Applicable
Ride Control	Optional
Radio Remote Control (SJC Required)	Optional
Reversing Fan	Optional
Rear Hydraulics	Optional
Horn	Standard